

Supersedes Date
25/07/2022

Revision date
10/01/2024

Revision Number
1
Country-Language: FIN-EN

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product Name Neste Marine 0.5
Product Code(s) 19235
Safety data sheet number 19235
Other means of identification 170739
REACH registration number 01-2119474894-22-0010
CAS No. 68476-33-5
Pure substance/mixture Substance

Contains Fuel oil, residual

1.2. Relevant identified uses of the substance or mixture and uses advised against

Recommended use Manufacture of substance
Distribution of substance
Formulation & (re)packing of substances and mixtures
Use as an intermediate
Use as a fuel
Uses advised against Professional: Uses in coatings
Professional: Road and construction applications

1.3. Details of the supplier of the safety data sheet

Supplier
Neste Oyj
Keilaranta 21, Espoo, P.O.B. 95, FIN-00095 NESTE, FINLAND
Tel. +358 10 45811
SDS@neste.com (chemical safety)

1.4. Emergency telephone number

Emergency Telephone No information available

Emergency Telephone - §45 - (EC)1272/2008	
Europe	112
Finland	+358 800 147 111, +358 9 471 977, Poison Information Centre
Germany	+49 32 211121704, Chemwatch Emergency Response Phone Number
Sweden	När det är akut: 112, begär giftinformation. I mindre akuta fall 010-456 6700, Giftinformationscentralens direktnummer

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Regulation (EC) No 1272/2008

Acute toxicity - Inhalation (Dusts/Mists)	Category 4 - (H332)
Carcinogenicity	Category 1B - (H350)
Reproductive toxicity	Category 2 - (H361d)
Specific target organ toxicity — repeated exposure	Category 2 - (H373)
Acute aquatic toxicity	Category 1 - (H400)
Chronic aquatic toxicity	Category 1 - (H410)

2.2. Label elements

Contains Fuel oil, residual

**Signal word**

Danger

Hazard statements

H332 - Harmful if inhaled

H350 - May cause cancer

H361d - Suspected of damaging the unborn child

H373 - May cause damage to organs through prolonged or repeated exposure

H410 - Very toxic to aquatic life with long lasting effects

EUH066 - Repeated exposure may cause skin dryness or cracking

Precautionary Statements - EU (§28, 1272/2008)

P260 - Do not breathe dust/fume/gas/mist/vapours/spray

P273 - Avoid release to the environment

P280 - Wear protective gloves/protective clothing/eye protection/face protection

P308 + P313 - IF exposed or concerned: Get medical advice/attention

2.3. Other hazards

Combustible liquid. Mainly non-volatile. Unloading gases. (hydrogen sulphide (H₂S), hydrocarbons):. Irritating to eyes. Irritating to respiratory system. High concentrations can depress the central nervous system. Contact with product at elevated temperatures can result in thermal burns.

This substance does not meet the PBT/vPvB criteria of REACH, annex XIII.

This product does not contain substances considered to have endocrine disrupting properties at levels of 0.1% or higher.

SECTION 3: Composition/information on ingredients**3.1 Substances****Chemical nature**

Max. Sulphur: 0.5 wt-%.

Chemical name	Weight-%	REACH registration number	EC No (EU Index No)	Classification according to Regulation (EC) No.	Specific concentration	M-Factor	M-Factor (long-term)
---------------	----------	---------------------------	---------------------	---	------------------------	----------	----------------------

				1272/2008 [CLP]	limit (SCL)		
Fuel oil, residual 68476-33-5	~ 100	01-2119474894-22-00 10	270-675-6	Acute Tox. 4 (H332) Aquatic Chronic 1 (H410) STOT RE 2 (H373) Repr. 2 (H361d) Aquatic Acute 1 (H400) Carc. 1B (H350)	-	1	1

Full text of H- and EUH-phrases: see section 16

This product does not contain candidate substances of very high concern at a concentration $\geq 0.1\%$ (Regulation (EC) No. 1907/2006 (REACH), Article 59)

Additional information

A petroleum product. Substance of Unknown or Variable composition, Complex reaction products or Biological materials (UVCB).

SECTION 4: First aid measures

4.1. Description of first aid measures

General advice	IF exposed or concerned: Get medical advice/attention. Show this safety data sheet to the doctor in attendance.
Inhalation	Obtain medical attention if oil mist is inhaled (risk of chemicals pneumonitis). Unloading gases. (hydrogen sulphide (H ₂ S), hydrocarbons):. Remove to fresh air. If symptoms persist, call a doctor. If breathing has stopped, give artificial respiration. Get medical attention immediately.
Eye contact	Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Do not rub affected area. Get medical attention if irritation develops and persists.
Skin contact	Wash skin with soap and water. Do not use solvents or thinners to dissolve the material. Take off contaminated clothing. Wash off immediately with plenty of water for at least 15 minutes. Get medical attention if irritation develops and persists.
Ingestion	Do NOT induce vomiting. Get medical attention if symptoms occur.
Self-protection of the first aider	Ensure that medical personnel are aware of the material(s) involved, take precautions to protect themselves and prevent spread of contamination. Avoid breathing vapours or mists. Use personal protective equipment as required. See section 8 for more information.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms	Repeated exposure may cause skin dryness or cracking. Harmful by inhalation. Oil mist may irritate eyes and respiratory tract. Unloading gases. (hydrogen sulphide (H ₂ S), hydrocarbons):. Causes eye irritation. Respiratory irritation. High concentrations can depress the central nervous system.
-----------------	---

4.3. Indication of any immediate medical attention and special treatment needed

Note to doctors	Treat symptomatically. Hydrogen sulphide (H ₂ S): . : May cause nausea, headache, dizziness and intoxication. Drowsiness.
------------------------	--

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable Extinguishing Media	Foam. Carbon dioxide (CO ₂). Dry chemical.
Large Fire	CAUTION: Use of water spray when fighting fire may be inefficient.
Unsuitable extinguishing media	Do not scatter spilled material with high pressure water streams.

5.2. Special hazards arising from the substance or mixture

Specific hazards arising from the chemical	Containers may explode when heated.
Hazardous combustion products	Carbon monoxide. Hydrogen sulphide. Oxides of sulphur. H ₂ SO ₄ .

5.3. Advice for firefighters

Special protective equipment and precautions for fire-fighters	Cool containers with flooding quantities of water until well after fire is out. Move containers from fire area if you can do it without risk. Prevent fire extinguishing water from contaminating surface water or the ground water system. Wear positive pressure self-contained breathing apparatus (SCBA). Use personal protection equipment.
---	--

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions	Use personal protective equipment as required. Avoid contact with skin, eyes or clothing. Avoid breathing vapours or mists. Ensure adequate ventilation. Do not touch or walk through spilled material.
For emergency responders	Evacuate area. Keep people away from and upwind of spill/leak. Prevent unauthorized access. Pay attention to the fire and health hazards caused by the product. ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area). Use personal protective equipment as required.

6.2. Environmental precautions

Environmental precautions	Risk of soil and ground water contamination. Avoid release to the environment. Keep out of drains, sewers, ditches and waterways.
----------------------------------	---

6.3. Methods and material for containment and cleaning up

Methods for containment	Inform the relevant authorities if environmental pollution occurs (sewers, waterways, soil or air). Stop leak if you can do it without risk.
Methods for cleaning up	Pay attention to the fire and health hazards caused by the product. Immediately start clean-up of the liquid and contaminated soil. Allow hot product solidify first (if there is no risk of spreading into the environment). Solid product can be taken up. Take up with sand or other noncombustible absorbent material and place into containers for later disposal. Stains can be cleaned with a hydrocarbon solvent.
Prevention of secondary hazards	Clean contaminated objects and areas thoroughly observing environmental regulations.

6.4. Reference to other sections

Reference to other sections	See Section 7 for more information, See section 8 for more information. See section 13 for more information.
------------------------------------	--

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

Remove all sources of ignition. Take precautionary measures against static discharges. Product is usually handled heated. When handling heated product wear thermally insulated protective equipment. Handling and storage temperature must not exceed the flash point. Avoid skin contact and inhalation of oil mist. Use personal protective equipment and/or local ventilation when needed.

Unloading gases. ∴ Avoid breathing vapours or mists. (H₂S, Hydrocarbons). Use only outdoors or in a well-ventilated area.

During tank operations follow special instructions (risk of oxygen displacement and hydrocarbons). Hydrogen sulphide.

General hygiene considerations

Do not eat, drink or smoke when using this product. Wash hands before breaks and immediately after handling the product. Handle in accordance with good industrial hygiene and safety practice.

7.2. Conditions for safe storage, including any incompatibilities

Storage Conditions

Flammable liquid storage. Can be stored heated. Store in a demarcated bunded area to prevent release to drains and/or watercourses. Change contaminated thermal insulation material (autoignition hazard).

7.3. Specific end use(s)

Risk Management Methods (RMM) The information required is contained in this Safety Data Sheet.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Exposure Limits

Oil mist: 5 mg/m³ (8h) HTP 2020/FIN. Hydrogen sulfide: 5 ppm (8h), 7 mg/m³ (8h), 10 ppm (15 min), 14 mg/m³ (15 min) HTP 2020/FIN, EU OELV (EC/2009/161).

Derived No Effect Level (DNEL) - Workers

Chemical name	Oral	Dermal	Inhalation
Fuel oil, residual 68476-33-5	-	0.065 mg/kg bw/day [4] [6]	0.18 mg/m ³ [4] [6] 4700 mg/m ³ [4] [7]

Notes

[4] Systemic health effects.
[6] Long term.
[7] Short term.

Derived No Effect Level (DNEL) - General Public

Notes

[4] Systemic health effects.
[6] Long term.

Predicted No Effect Concentration (PNEC)

Chemical name	Freshwater sediment	Marine sediment	Sewage treatment	Soil	Food chain
Fuel oil, residual 68476-33-5	-	-	-	-	66.7 mg/kg (food, secondary poisoning)

8.2. Exposure controls**Engineering controls**

Provide adequate ventilation. Use personal protective equipment and/or local ventilation when needed. Product is usually handled heated. When handling heated product wear thermally insulated protective equipment. During tank operations follow special instructions (risk of oxygen displacement and hydrocarbons).

Personal protective equipment**Eye/face protection**

Tight sealing safety goggles. Face shield when needed.

Hand protection

Thick, thermally insulated protective gloves. PPE - Glove material. ∴ Polyvinyl chloride (PVC). Nitrile rubber. Change protective gloves regularly. Protective gloves according to standards EN 374 and EN 407.

Skin and body protection

Protective clothing when needed. When handling heated product wear thermally insulated protective equipment.

Respiratory protection

Filter must be changed often enough. Gas and combination filter cartridges must comply with EN 14387. Wear a respirator fitted with the following cartridge: ∴ Combination filter, type A2/P3. Filter device could be used maximum 2 hours at a time. Filter devices must not be used in conditions where the oxygen level is low (< 19 vol.-%). At high concentrations a breathing apparatus must be used (self-contained or fresh air hose breathing apparatus).

General hygiene considerations

Do not eat, drink or smoke when using this product. Wash hands before breaks and immediately after handling the product. Handle in accordance with good industrial hygiene and safety practice.

Environmental exposure controls

Store in a demarcated bunded area to prevent release to drains and/or watercourses. Take precautions against leakage by constructing collecting pools and sewerage systems as well as by surfacing the loading and unloading stations.

SECTION 9: Physical and chemical properties**9.1. Information on basic physical and chemical properties**

Physical state	Liquid
Colour	black
Odour	Strong. Characteristic.
Odour threshold	No information available

Property	Values	Remarks • Method
Melting point / freezing point	< 30 °C	Pour Point (ISO 3016)
Initial boiling point and boiling range	150 - > 750 °C	None known
Flammability	No data available	None known

Flammability Limit in Air		None known
Upper flammability or explosive limits	~ 6 %	
Lower flammability or explosive limits	~ 1 %	
Flash point	>= 65 °C	EN ISO 2719
Autoignition temperature	> 400 °C	None known
Decomposition temperature		None known
pH	No data available	None known
pH (as aqueous solution)	No data available	None known
Kinematic viscosity	150 - 300 mm ² /s	@ 50 °C (EN ISO 3104) typical value (calculated)
Dynamic viscosity	No data available	None known
Water solubility	The product has poor water-solubility.	None known
Solubility(ies)	No data available	None known
Partition coefficient	log Kow: 4 - > 6	None known
Vapour pressure	< 1 kPa	@ 38 °C
Relative density	0.92 - 0.991	@ 15 °C (EN ISO 12185, EN ISO 3675) typical value
Bulk density	No data available	
Liquid Density	No data available	
Relative vapour density	No data available	None known
Particle characteristics		
Particle Size	Not applicable	
Particle Size Distribution	Not applicable	

9.2. Other information

9.2.1. Information with regards to physical hazard classes

Not applicable

Explosive properties

Not considered to be explosive

Oxidising properties

Does not meet the criteria for classification as oxidising

9.2.2. Other safety characteristics

No information available

SECTION 10: Stability and reactivity

10.1. Reactivity

Reactivity

There are no known reactivity hazards associated with this product.

10.2. Chemical stability

Stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

Possibility of hazardous reactions

None under normal processing.

10.4. Conditions to avoid

Conditions to avoid

Heat, flames and sparks.

10.5. Incompatible materials

Incompatible materials

Oxidising agent.

10.6. Hazardous decomposition products

Hazardous decomposition products Hydrogen sulphide.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Information on likely routes of exposure

Acute toxicity Harmful if inhaled

Numerical measures of toxicity

Based on available data, the classification criteria are not met

Component Information

Chemical name	Oral LD50	Dermal LD50	Inhalation LC50
Fuel oil, residual	4320 - 5270 mg/kg, Rat (OECD 401)	> 2000 mg/kg, Rabbit (EC B.3, OECD 434)	4100 mg/m ³ , Rat (EPA OTS 798.1150)

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Skin corrosion/irritation Based on available data, the classification criteria are not met. Repeated exposure may cause skin dryness or cracking. (OECD 404).

Serious eye damage/eye irritation Based on available data, the classification criteria are not met. (EC B.5).

Respiratory or skin sensitisation Based on available data, the classification criteria are not met. (OECD 406).

Germ cell mutagenicity Based on available data, the classification criteria are not met. (EC B.12, OECD 471, 476, 475).

Carcinogenicity May cause cancer. (OECD 451).

The table below indicates whether each agency has listed any ingredient as a carcinogen.

Chemical name	European Union
Fuel oil, residual	Carc. 1B

Reproductive toxicity Suspected of damaging the unborn child. (EPA OTS 798.4900).

STOT - single exposure Based on available data, the classification criteria are not met.

STOT - repeated exposure May cause damage to organs through prolonged or repeated exposure. (EPA OPPTS

870.3250).

Aspiration hazard Based on available data, the classification criteria are not met.

11.2. Information on other hazards

11.2.1. Endocrine disrupting properties

Endocrine disrupting properties This product does not contain substances considered to have endocrine disrupting properties at levels of 0.1% or higher.

11.2.2. Other information

Other adverse effects Especially fresh product may contain traces of highly toxic hydrogen sulphide, which irritates severely eyes and respiratory tract. High concentrations can depress the central nervous system. The product contains traces of nickel and vanadium compounds, which are hazardous to health.

SECTION 12: Ecological information

12.1. Toxicity

Ecotoxicity Very toxic to aquatic life with long lasting effects. $0.1 < L(E)C50 \leq 1$.

Chemical name	Algae/aquatic plants	Fish	Toxicity to microorganisms	Crustacea
Fuel oil, residual	OECD 201, 72 hours, Pseudokirchneriella subcapitata, WAF EL50: 0,32 mg/l EPA-600/9-018, 72 hours, Pseudokirchneriella subcapitata, WAF NOELR: 0,05 mg/l	OECD 203, 96 hours, Oncorhynchus mykiss (Rainbow trout), WAF LL ₅₀ : 79 mg/l QSAR (Heavy fuel oil), 28 days, Oncorhynchus mykiss (Rainbow trout) NOEL: 0,1 mg/l	QSAR (Heavy fuel oil), 72 hours, Micro-organisms (wastewater sludge), Tetrahymena pyriformis: LL ₅₀ : > 1000 mg/l NOEL: 14,9 mg/l	OECD 202, 48 hours, Daphnia magna, WAF: EL50: 0,22 mg/l QSAR (Heavy fuel oil) 21 days, Daphnia magna: NOEL: 0,27 mg/l

12.2. Persistence and degradability

Persistence and degradability The product is slowly degradable. Lightest hydrocarbons are volatile.

12.3. Bioaccumulative potential

Bioaccumulation May bioaccumulate.

12.4. Mobility in soil

Mobility in soil Insoluble in water. Mainly non-volatile. The product contains substances which are bound to particulate matter and are retained in soil.

12.5. Results of PBT and vPvB assessment

PBT and vPvB assessment The product does not contain any substance(s) classified as PBT or vPvB above the threshold of declaration.

Chemical name	PBT and vPvB assessment
Fuel oil, residual	The substance is not PBT / vPvB

12.6. Endocrine disrupting properties

Endocrine disrupting properties This product does not contain substances considered to have endocrine disrupting properties at levels of 0.1% or higher.

12.7. Other adverse effects

Product causes fouling, and direct contact produces harmful effects e.g. to birds and vegetation. Adsorbed hydrocarbon residues can be harmful to sediment organisms.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste from residues/unused products Dispose of in accordance with local regulations. Dispose of waste in accordance with environmental legislation. Care should be taken when handling emptied containers that have not been thoroughly cleaned or rinsed out. When handling waste, the safety precautions applying to handling of the product should be considered.

Contaminated packaging Do not reuse empty containers.

SECTION 14: Transport information

IMDG

14.1 UN number or ID number	UN3082
14.2 UN proper shipping name	UN3082 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.(FUEL OIL)
14.3 Transport hazard class(es)	9
14.4 Packing group	III
14.5 Environmental hazard	Marine pollutant
14.6 Special precautions for user	.
Special Provisions	-
14.7 Maritime transport in bulk according to IMO instruments	No

RID

14.1 UN number or ID number	UN3082
14.2 UN proper shipping name	UN 3082, ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (FUEL OIL)
14.3 Transport hazard class(es)	9
14.4 Packing group	III
14.5 Environmental hazard	Marine pollutant
14.6 Special precautions for user	.
Classification code	90

ADR

14.1 UN number or ID number	UN3082
14.2 UN proper shipping name	UN3082 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.(FUEL OIL)
14.3 Transport hazard class(es)	9
14.4 Packing group	III
14.5 Environmental hazard	Marine pollutant
14.6 Special precautions for user	.

Classification code 90
Tunnel restriction code (-)

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

National regulations

European Union

Take note of Directive 98/24/EC on the protection of the health and safety of workers from the risks related to chemical agents at work.

Authorisations and/or restrictions on use:

This product contains one or more substance(s) subject to restriction (Regulation (EC) No. 1907/2006 (REACH), Annex XVII)

Chemical name	Restricted substance per REACH Annex XVII	Substance subject to authorisation per REACH Annex XIV
Fuel oil, residual - 68476-33-5	28. 75.	-

Persistent Organic Pollutants

Not applicable

Dangerous substance category per Seveso Directive (2012/18/EU)

E1 - Hazardous to the Aquatic Environment in Category Acute 1 or Chronic 1

Named dangerous substances per Seveso Directive (2012/18/EU)

Chemical name	Lower-tier requirements (tons)	Upper-tier requirements (tons)
Fuel oil, residual - 68476-33-5	-	25000

Ozone-depleting substances (ODS) regulation (EC) 1005/2009

Not applicable

Other Regulations

Safety Data Sheet according to Regulation (EC) No. 1907/2006 (REACH). Classification according to Regulation (EC) No. 1272/2008 [CLP].

15.2. Chemical safety assessment

Chemical Safety Report

Chemical Safety Assessments have been carried out for these substances

SECTION 16: Other information

Key or legend to abbreviations and acronyms used in the safety data sheet

Full text of H-Statements referred to under section 3

H332 - Harmful if inhaled

H350 - May cause cancer

H361d - Suspected of damaging the unborn child

H373 - May cause damage to organs through prolonged or repeated exposure

H400 - Very toxic to aquatic life

H410 - Very toxic to aquatic life with long lasting effects

Legend

SVHC: Substances of Very High Concern for Authorisation:

Legend Section 8: Exposure controls/personal protection

TWA TWA (time-weighted average)

STEL

STEL (Short Term Exposure Limit)

Ceiling Maximum limit value

*

Skin designation

+ Sensitisers

Classification procedure	
Classification according to Regulation (EC) No. 1272/2008 [CLP]	Method Used
Acute oral toxicity	Calculation method
Acute dermal toxicity	Calculation method
Acute inhalation toxicity - gas	Calculation method
Acute inhalation toxicity - vapour	Calculation method
Acute inhalation toxicity - dust/mist	Calculation method
Skin corrosion/irritation	Calculation method
Serious eye damage/eye irritation	Calculation method
Respiratory sensitisation	Calculation method
Skin sensitisation	Calculation method
Mutagenicity	Calculation method
Carcinogenicity	Calculation method
STOT - single exposure	Calculation method
STOT - repeated exposure	Calculation method
Acute aquatic toxicity	Calculation method
Chronic aquatic toxicity	Calculation method
Aspiration hazard	Calculation method
Ozone	Calculation method

Supersedes Date 25/07/2022

Revision date 10/01/2024

Reason for revision This is the first issue. (new SDS software has been introduced)

Safety Data Sheet according to Regulation (EC) No. 1907/2006 (REACH)**Disclaimer**

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

End of Safety Data Sheet

Exposure scenario

Use of Substance as Intermediate - Industrial

Identification

Product name	Fuel oil, residual
CAS number	68476-33-5
EC number	270-675-6
Version number	2018
Es reference	ES01b

1. Title of exposure scenario

Main title	Use of Substance as Intermediate - Industrial
Process scope	Use of substance as an intermediate (not related to Strictly Controlled Conditions). Includes recycling/recovery, material transfers, storage, sampling, associated laboratory activities, maintenance and loading (including marine vessel/barge, road/rail car and bulk container).
Sector of use	SU8 Manufacture of bulk, large-scale chemicals (including petroleum products) SU9 Manufacture of fine chemicals
<u>Environment</u>	
Environmental release category	ERC6a Use of intermediate
SPERC	ESVOC SPERC 6.1a.v1
<u>Worker</u>	
Process category	PROC1 Chemical production or refinery in closed process without likelihood of exposure or processes with equivalent containment conditions PROC2 Chemical production or refinery in closed continuous process with occasional controlled exposure or processes with equivalent containment conditions PROC3 Manufacture or formulation in the chemical industry in closed batch processes with occasional controlled exposure or processes with equivalent containment condition PROC8a Transfer of substance or mixture (charging and discharging) at non-dedicated facilities PROC8b Transfer of substance or mixture (charging and discharging) at dedicated facilities PROC15 Use as laboratory reagent.

2. Conditions of use affecting exposure (Industrial - Environment 1)

Product characteristics

Substance is complex UVCB. Predominantly hydrophobic.

Amounts used

Fraction of EU tonnage used in region: 0.1
Regional use tonnage: 1.8E+06 tonnes/year
Fraction of Regional tonnage used locally: 8.3E-03
Annual site tonnage: 1.5E+04 tonnes
Maximum daily site tonnage: 5.0E+04 kg

Frequency and duration of use

Continuous release.
Emission days: 300 days/year

Use of Substance as Intermediate - Industrial

Other given operational conditions affecting environmental exposure

Emission factor - air	Release fraction to air from process (initial release prior to RMM): 1.0E-04
Emission factor - water	Release fraction to wastewater from process (initial release prior to RMM): 9.9E-07
Emission factor - soil	Release fraction to soil from process (initial release prior to RMM): 0.001

Environmental factors not influenced by risk management measures

Dilution	Local freshwater dilution factor: 10 Local marine water dilution factor: 100
----------	---

Risk management measures

Good practice	Common practices vary across sites, thus conservative process release estimates used. Risk from environmental exposure is driven by terrestrial secondary poisoning.
STP details	Not applicable as there is no release to wastewater. Estimated substance removal from wastewater via domestic sewage treatment: 94.2% Total efficiency of removal from wastewater after onsite and offsite (domestic treatment plant) RMMs: 94.2% Maximum allowable site tonnage (M _{safe}), based on release following total wastewater treatment removal: 7.3E+04 kg/day Assumed domestic sewage treatment plant flow (m ³ /day): 2000.

Technical onsite conditions and measures to reduce or limit discharges to air, water and soil

Air	Treat air emission to provide a typical removal efficiency of 80%.
Water	If discharging to domestic sewage treatment plant, no onsite wastewater treatment required. Treat onsite wastewater (prior to receiving water discharge) to provide the required removal efficiency of (%): ≥ 0.0 . If discharging to domestic sewage treatment plant, provide the required onsite wastewater removal efficiency of $\geq 0.0\%$. Prevent discharge of undissolved substance to or recover from onsite waste water.
Soil	Do not apply industrial sludge to natural soils. Sludge should be incinerated, contained or reclaimed.

Conditions and measures related to external treatment of waste for disposal

Waste treatment	This substance is consumed during use and no waste of the substance is generated.
-----------------	---

Conditions and measures related to external recovery of waste

Recovery method	This substance is consumed during use and no waste of the substance is generated.
-----------------	---

2. Conditions of use affecting exposure (Workers - Health 1)

Product characteristics

Physical state	Liquid
Vapour pressure	Vapour pressure < 0.5 kPa at STP.
Concentration details	Covers percentage substance in the product up to 100% (unless stated differently).

Frequency and duration of use

Covers daily exposures up to 8 hours (unless stated differently).

Other given operational conditions affecting workers exposure

Setting	Assumes a good basic standard of occupational hygiene is implemented.
Temperature	Operation is carried out at elevated temperature (> 20°C above ambient temperature).

Use of Substance as Intermediate - Industrial

Organisational measures to prevent/limit releases, dispersion and exposure

Organisational measures General measures (carcinogens) Consider technical advances and process upgrades (including automation) for the elimination of releases. minimise exposure using measures such as closed systems, dedicated facilities and suitable general/local exhaust ventilation. Drain down systems and clear transfer lines prior to breaking containment. Clean/flush equipment, where possible, prior to maintenance Where there is potential for exposure: restrict access to authorised persons; provide specific activity training to operators to minimise exposures; wear suitable gloves and coveralls to prevent skin contamination; wear respiratory protection when its use is identified for certain contributing scenario; clear up spills immediately and dispose of waste safely. Ensure safe systems of work or equivalent arrangements are in place to manage risks. Regularly inspect, test and maintain all control measures. Consider the need for risk based health surveillance.

Risk management measures

Use of Substance as Intermediate - Industrial

General exposures (closed systems)

Handle substance within a closed system.

Wear chemically-resistant gloves (tested to EN374) in combination with 'basic' employee training.

.

Process sampling

Outdoor.

Handle substance within a closed system.

Sample via a closed loop or other system to avoid exposure.

Avoid carrying out activities involving exposure for more than 15 minutes.

Wear chemically-resistant gloves (tested to EN374) in combination with 'basic' employee training.

.

Bulk product storage

Store substance within a closed system.

Avoid carrying out activities involving exposure for more than 4 hours.

Wear chemically-resistant gloves (tested to EN374) in combination with 'basic' employee training.

.

Laboratory activities

Handle within a fume cupboard or implement suitable equivalent methods to minimise exposure.

Wear suitable gloves tested to EN374.

.

Marine vessel/barge (un)loading.

Avoid carrying out activities involving exposure for more than 4 hours.

Transfer via enclosed lines.

Clear transfer lines prior to de-coupling.

Retain drain-downs in sealed storage pending disposal or for subsequent recycle.

Wear chemically-resistant gloves (tested to EN374) in combination with 'basic' employee training.

.

Road tanker/rail car loading.

Ensure material transfers are under containment or extract ventilation.

Wear chemically-resistant gloves (tested to EN374) in combination with 'basic' employee training.

.

Equipment cleaning and maintenance

Drain down and flush system prior to equipment break-in or maintenance.

Wear chemically-resistant gloves (tested to EN374) in combination with specific activity training.

Retain drain-downs in sealed storage pending disposal or for subsequent recycle.

3. Exposure estimation (Environment 1)

Assessment method	Used Petrorisk model. (Hydrocarbon Block Method)
	Risk-driving RCR - air compartment driven 6.9E-01
	Risk-driving RCR - water compartment driven 1.1E-02

4. Guidance to check compliance with the exposure scenario (Environment 1)

Use of Substance as Intermediate - Industrial

Guidance is based on assumed operating conditions which may not be applicable to all sites, thus, scaling may be necessary to define appropriate site-specific risk management measures. Required removal efficiency for wastewater can be achieved using onsite/offsite technologies, either alone or in combination. Required removal efficiency for air can be achieved using onsite technologies, either alone or in combination. Further details on scaling and control technologies are provided in SpERC factsheet (<http://cefic.org/en/reach-for-industries-libraries.html>).

3. Exposure estimation (Health 1)

Assessment method

The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise indicated

Available hazard data do not enable the derivation of a DNEL for carcinogenic effects. Available hazard data do not support the need for a DNEL to be established for other health effects. Qualitative approach used to conclude safe use.

4. Guidance to check compliance with the exposure scenario (Health 1)

Predicted exposures are not expected to exceed the DN(M)EL when the Risk Management Measures/Operational Conditions outlined in Section 2 are implemented. Where other Risk Management Measures/Operational Conditions are adopted, then users should ensure that risks are managed to at least equivalent levels.

Exposure scenario

Distribution of Substance - Industrial

Identification

Product name	Fuel oil, residual
CAS number	68476-33-5
EC number	270-675-6
Version number	2018
Es reference	ES01a

1. Title of exposure scenario

Main title	Distribution of Substance - Industrial
Process scope	Loading (including marine vessel/barge, rail/road car and IBC loading) and repacking (including drums and small packs) of substance, including its sampling, storage, unloading distribution and associated laboratory activities.
Sector of use	NA
<u>Environment</u>	
Environmental release category	ERC4 Use of non-reactive processing aid at industrial site (no inclusion into or onto article) ERC5 Use at industrial site leading to inclusion into/onto article ERC6a Use of intermediate ERC6b Use of reactive processing aid at industrial site (no inclusion into or onto article) ERC6c Use of monomer in polymerisation processes at industrial site (inclusion or not into/onto article) ERC6d Use of reactive process regulators in polymerisation processes at industrial site (inclusion or not into/onto article) ERC7 Use of functional fluid at industrial site
SPERC	ESVOC SPERC 1.1b.v1
<u>Worker</u>	
Process category	PROC1 Chemical production or refinery in closed process without likelihood of exposure or processes with equivalent containment conditions PROC2 Chemical production or refinery in closed continuous process with occasional controlled exposure or processes with equivalent containment conditions PROC3 Manufacture or formulation in the chemical industry in closed batch processes with occasional controlled exposure or processes with equivalent containment condition PROC8a Transfer of substance or mixture (charging and discharging) at non-dedicated facilities PROC8b Transfer of substance or mixture (charging and discharging) at dedicated facilities PROC15 Use as laboratory reagent.

2. Conditions of use affecting exposure (Industrial - Environment 1)

Product characteristics

Substance is complex UVCB. Predominantly hydrophobic.

Amounts used

Distribution of Substance - Industrial

Fraction of EU tonnage used in region: 0.1
Regional use tonnage: 9.3E+06 tonnes/year
Fraction of Regional tonnage used locally: 2.0E-03
Annual site tonnage: 1.9E+04 tonnes
Maximum daily site tonnage: 6.2E+04 kg

Frequency and duration of use

Continuous release.
Emission days: 300 days/year

Other given operational conditions affecting environmental exposure

Emission factor - air Release fraction to air from process (initial release prior to RMM): 1.0E-03
Emission factor - water Release fraction to wastewater from process (initial release prior to RMM): 1.0E-06
Emission factor - soil Release fraction to soil from process (initial release prior to RMM): 0.00001

Environmental factors not influenced by risk management measures

Dilution Local freshwater dilution factor: 10
Local marine water dilution factor: 100

Risk management measures

Good practice Common practices vary across sites, thus conservative process release estimates used.
Risk from environmental exposure is driven by terrestrial secondary poisoning.

STP details Not applicable as there is no release to wastewater.
Estimated substance removal from wastewater via domestic sewage treatment: 94.2%
Total efficiency of removal from wastewater after onsite and offsite (domestic treatment plant) RMMs: 94.2%
Maximum allowable site tonnage (M_{safe}), based on release following total wastewater treatment removal: 8.9E+04 kg/day
Assumed domestic sewage treatment plant flow (m³/day): 2000.

Technical onsite conditions and measures to reduce or limit discharges to air, water and soil

Air Treat air emission to provide a typical removal efficiency of 90%.
Water No wastewater treatment required. Treat onsite wastewater (prior to receiving water discharge) to provide the required removal efficiency of (%): ≥ 0.0 . If discharging to domestic sewage treatment plant, provide the required onsite wastewater removal efficiency of 0.0%.
Soil Do not apply industrial sludge to natural soils. Sludge should be incinerated, contained or reclaimed.

Conditions and measures related to external treatment of waste for disposal

Waste treatment External treatment and disposal of waste should comply with applicable local and/or national regulations.

Conditions and measures related to external recovery of waste

Recovery method External recovery and recycling of waste should comply with applicable local and/or national regulations.

2. Conditions of use affecting exposure (Workers - Health 1)

Product characteristics

Physical state Liquid

Distribution of Substance - Industrial

Vapour pressure	Vapour pressure < 0.5 kPa at STP.
Concentration details	Covers percentage substance in the product up to 100% (unless stated differently).
<u>Frequency and duration of use</u>	Covers daily exposures up to 8 hours (unless stated differently).
<u>Other given operational conditions affecting workers exposure</u>	
Setting	Assumes a good basic standard of occupational hygiene is implemented.
Temperature	Assumes use at not more than 20°C above ambient temperature, unless stated differently.
<u>Organisational measures to prevent/limit releases, dispersion and exposure</u>	
Organisational measures	General measures (carcinogens) Consider technical advances and process upgrades (including automation) for the elimination of releases. minimise exposure using measures such as closed systems, dedicated facilities and suitable general/local exhaust ventilation. Drain down systems and clear transfer lines prior to breaking containment. Clean/flush equipment, where possible, prior to maintenance Where there is potential for exposure: restrict access to authorised persons; provide specific activity training to operators to minimise exposures; wear suitable gloves and coveralls to prevent skin contamination; wear respiratory protection when its use is identified for certain contributing scenario; clear up spills immediately and dispose of waste safely. Ensure safe systems of work or equivalent arrangements are in place to manage risks. Regularly inspect, test and maintain all control measures. Consider the need for risk based health surveillance.
<u>Risk management measures</u>	

Distribution of Substance - Industrial

Process sampling

Outdoor.

Sample via a closed loop or other system to avoid exposure.

Avoid carrying out activities involving exposure for more than 15 minutes.

Wear chemically-resistant gloves (tested to EN374) in combination with 'basic' employee training.

.

General exposures (closed systems)

Handle substance within a closed system.

Avoid carrying out activities involving exposure for more than 4 hours.

Sample via a closed loop or other system to avoid exposure.

Wear chemically-resistant gloves (tested to EN374) in combination with 'basic' employee training.

.

Bulk product storage

Store substance within a closed system.

Avoid carrying out activities involving exposure for more than 4 hours.

Wear chemically-resistant gloves (tested to EN374) in combination with 'basic' employee training.

.

Product sampling

Sample via a closed loop or other system to avoid exposure.

Avoid carrying out activities involving exposure for more than 15 minutes.

Wear chemically-resistant gloves (tested to EN374) in combination with 'basic' employee training.

.

Laboratory activities

Handle within a fume cupboard or implement suitable equivalent methods to minimise exposure.

Wear suitable gloves tested to EN374.

.

Marine vessel/barge (un)loading.

Avoid carrying out activities involving exposure for more than 4 hours.

Transfer via enclosed lines.

Clear transfer lines prior to de-coupling.

Retain drain-downs in sealed storage pending disposal or for subsequent recycle.

Wear chemically-resistant gloves (tested to EN374) in combination with 'basic' employee training.

.

Road tanker/rail car loading.

Ensure material transfers are under containment or extract ventilation.

Wear chemically-resistant gloves (tested to EN374) in combination with 'basic' employee training.

.

Equipment cleaning and maintenance

Drain down and flush system prior to equipment break-in or maintenance.

Wear chemically-resistant gloves (tested to EN374) in combination with specific activity training.

Retain drain-downs in sealed storage pending disposal or for subsequent recycle.

Distribution of Substance - Industrial

Assessment method	Used Petrorisk model. (Hydrocarbon Block Method)
	Maximum Risk Characterisation Ratios for air emissions 7.0E-01
	Maximum Risk Characterisation Ratios for wastewater emissions 1.3E-02

4. Guidance to check compliance with the exposure scenario (Environment 1)

Guidance is based on assumed operating conditions which may not be applicable to all sites, thus, scaling may be necessary to define appropriate site-specific risk management measures. Required removal efficiency for wastewater can be achieved using onsite/offsite technologies, either alone or in combination. Required removal efficiency for air can be achieved using onsite technologies, either alone or in combination. Further details on scaling and control technologies are provided in SpERC factsheet (<http://cefic.org/en/reach-for-industries-libraries.html>).

3. Exposure estimation (Health 1)

Assessment method	The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise indicated
	Available hazard data do not enable the derivation of a DNEL for carcinogenic effects. Available hazard data do not support the need for a DNEL to be established for other health effects. Qualitative approach used to conclude safe use.

4. Guidance to check compliance with the exposure scenario (Health 1)

Predicted exposures are not expected to exceed the DN(M)EL when the Risk Management Measures/Operational Conditions outlined in Section 2 are implemented. Where other Risk Management Measures/Operational Conditions are adopted, then users should ensure that risks are managed to at least equivalent levels.

Exposure scenario

Formulation & (Re)packing of Substances and Mixtures - Industrial

Identification

Product name	Fuel oil, residual
CAS number	68476-33-5
EC number	270-675-6
Version number	2018
Es reference	ES02

1. Title of exposure scenario

Main title	Formulation & (Re)packing of Substances and Mixtures - Industrial
Process scope	Formulation, packing and re-packing of the substance and its mixtures in batch or continuous operations, including storage, materials transfers, mixing, tableting, compression, pelletisation, extrusion, large and small scale packing, sampling, maintenance and associated laboratory activities.
Sector of use	NA
Environment	
Environmental release category	ERC2 Formulation into mixture
SPERC	ESVOC SPERC 2.2.v1
Worker	
Process category	PROC1 Chemical production or refinery in closed process without likelihood of exposure or processes with equivalent containment conditions PROC2 Chemical production or refinery in closed continuous process with occasional controlled exposure or processes with equivalent containment conditions PROC3 Manufacture or formulation in the chemical industry in closed batch processes with occasional controlled exposure or processes with equivalent containment condition PROC8a Transfer of substance or mixture (charging and discharging) at non-dedicated facilities PROC8b Transfer of substance or mixture (charging and discharging) at dedicated facilities PROC15 Use as laboratory reagent.

2. Conditions of use affecting exposure (Industrial - Environment 1)

Product characteristics

Substance is complex UVCB. Predominantly hydrophobic.

Amounts used

Fraction of EU tonnage used in region: 0.1
Regional use tonnage: 7.5E+06 tonnes/year
Fraction of Regional tonnage used locally: 4.0E-03
Annual site tonnage: 3.0E+04 tonnes
Maximum daily site tonnage: 100 tonnes

Frequency and duration of use

Continuous release.
Emission days: 300 days/year

Formulation & (Re)packing of Substances and Mixtures - Industrial

Other given operational conditions affecting environmental exposure

Emission factor - air	Release fraction to air from process (after typical onsite RMMs consistent with EU Solvent Emissions Directive requirements): 2.5E-03
Emission factor - water	Release fraction to wastewater from process (initial release prior to RMM): 9.5E-06
Emission factor - soil	Release fraction to soil from process (initial release prior to RMM): 0.0001

Environmental factors not influenced by risk management measures

Dilution	Local freshwater dilution factor: 10 Local marine water dilution factor: 100
-----------------	---

Risk management measures

Good practice	Common practices vary across sites, thus conservative process release estimates used. Risk from environmental exposure is driven by terrestrial secondary poisoning.
----------------------	---

STP details	Not applicable as there is no release to wastewater. Estimated substance removal from wastewater via domestic sewage treatment: 94.2% Total efficiency of removal from wastewater after onsite and offsite (domestic treatment plant) RMMs: 94.2% Maximum allowable site tonnage (Msafe), based on release following total wastewater treatment removal: 1.1E+05 kg/day Assumed domestic sewage treatment plant flow (m ³ /day): 2000.
--------------------	---

Technical onsite conditions and measures to reduce or limit discharges to air, water and soil

Air	Treat air emission to provide a typical removal efficiency of 0%.
Water	Treat onsite wastewater (prior to receiving water discharge) to provide the required removal efficiency of (%): ≥ 60.9. If discharging to domestic sewage treatment plant, provide the required onsite wastewater removal efficiency of 0.0%. Prevent discharge of undissolved substance to or recover from onsite waste water. If discharging to domestic sewage treatment plant, no onsite wastewater treatment required.
Soil	Do not apply industrial sludge to natural soils. Sludge should be incinerated, contained or reclaimed.

Conditions and measures related to external treatment of waste for disposal

Waste treatment	External treatment and disposal of waste should comply with applicable local and/or national regulations.
------------------------	---

Conditions and measures related to external recovery of waste

Recovery method	External recovery and recycling of waste should comply with applicable local and/or national regulations.
------------------------	---

2. Conditions of use affecting exposure (Workers - Health 1)

Product characteristics

Physical state	Liquid
Vapour pressure	Vapour pressure < 0.5 kPa at STP.
Concentration details	Covers percentage substance in the product up to 100% (unless stated differently).

Frequency and duration of use

Covers daily exposures up to 8 hours (unless stated differently).

Other given operational conditions affecting workers exposure

Formulation & (Re)packing of Substances and Mixtures - Industrial

Setting Assumes a good basic standard of occupational hygiene is implemented.

Temperature Assumes use at not more than 20°C above ambient temperature, unless stated differently.

Organisational measures to prevent/limit releases, dispersion and exposure

Organisational measures General measures (carcinogens) Consider technical advances and process upgrades (including automation) for the elimination of releases. minimise exposure using measures such as closed systems, dedicated facilities and suitable general/local exhaust ventilation. Drain down systems and clear transfer lines prior to breaking containment. Clean/flush equipment, where possible, prior to maintenance Where there is potential for exposure: restrict access to authorised persons; provide specific activity training to operators to minimise exposures; wear suitable gloves and coveralls to prevent skin contamination; wear respiratory protection when its use is identified for certain contributing scenario; clear up spills immediately and dispose of waste safely. Ensure safe systems of work or equivalent arrangements are in place to manage risks. Regularly inspect, test and maintain all control measures. Consider the need for risk based health surveillance.

Risk management measures

Formulation & (Re)packing of Substances and Mixtures - Industrial

General exposures (closed systems)

Process sampling

Handle substance within a closed system.

Sample via a closed loop or other system to avoid exposure.

Avoid carrying out activities involving exposure for more than 15 minutes.

Wear chemically-resistant gloves (tested to EN374) in combination with 'basic' employee training.

.

General exposures (closed systems)

Handle substance within a closed system.

Sample via a closed loop or other system to avoid exposure.

Avoid carrying out activities involving exposure for more than 4 hours.

Wear chemically-resistant gloves (tested to EN374) in combination with 'basic' employee training.

.

Bulk product storage

Store substance within a closed system.

Avoid carrying out activities involving exposure for more than 4 hours.

Wear chemically-resistant gloves (tested to EN374) in combination with 'basic' employee training.

.

Product sampling

Sample via a closed loop or other system to avoid exposure.

Avoid carrying out activities involving exposure for more than 15 minutes.

Wear chemically-resistant gloves (tested to EN374) in combination with 'basic' employee training.

.

Laboratory activities

Handle within a fume cupboard or implement suitable equivalent methods to minimise exposure.

Wear suitable gloves tested to EN374.

.

Marine vessel/barge (un)loading.

Transfer via enclosed lines.

Avoid carrying out activities involving exposure for more than 4 hours.

Clear transfer lines prior to de-coupling.

Retain drain-downs in sealed storage pending disposal or for subsequent recycle.

Wear chemically-resistant gloves (tested to EN374) in combination with 'basic' employee training.

.

Road tanker/rail car loading.

Ensure material transfers are under containment or extract ventilation.

Wear chemically-resistant gloves (tested to EN374) in combination with 'basic' employee training.

.

Drum/batch transfers

Ensure material transfers are under containment or extract ventilation.

Provide a good standard of general ventilation (not less than 3 to 5 air changes per hour).

, or:

Ensure operation is undertaken outdoors.

Avoid carrying out activities involving exposure for more than 1 hour.

Wear chemically-resistant gloves (tested to EN374) in combination with 'basic' employee training.

.

Equipment cleaning and maintenance

Formulation & (Re)packing of Substances and Mixtures - Industrial

Drain down and flush system prior to equipment break-in or maintenance.
Wear chemically-resistant gloves (tested to EN374) in combination with specific activity training.
Retain drain-downs in sealed storage pending disposal or for subsequent recycle.

3. Exposure estimation (Environment 1)

Assessment method	Used Petrorisk model. (Hydrocarbon Block Method)
	Maximum Risk Characterisation Ratios for air emissions 7.0E-01
	Maximum Risk Characterisation Ratios for wastewater emissions 1.5E-01

4. Guidance to check compliance with the exposure scenario (Environment 1)

Guidance is based on assumed operating conditions which may not be applicable to all sites, thus, scaling may be necessary to define appropriate site-specific risk management measures. Required removal efficiency for wastewater can be achieved using onsite/offsite technologies, either alone or in combination. Required removal efficiency for air can be achieved using onsite technologies, either alone or in combination. Further details on scaling and control technologies are provided in SpERC factsheet (<http://cefic.org/en/reach-for-industries-libraries.html>).

3. Exposure estimation (Health 1)

Assessment method	The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise indicated
	Available hazard data do not enable the derivation of a DNEL for carcinogenic effects.
	Available hazard data do not support the need for a DNEL to be established for other health effects. Qualitative approach used to conclude safe use.

4. Guidance to check compliance with the exposure scenario (Health 1)

Predicted exposures are not expected to exceed the DN(M)EL when the Risk Management Measures/Operational Conditions outlined in Section 2 are implemented. Where other Risk Management Measures/Operational Conditions are adopted, then users should ensure that risks are managed to at least equivalent levels.

Exposure scenario

Use as a Fuel - Industrial

Identification

Product name	Fuel oil, residual
CAS number	68476-33-5
EC number	270-675-6
Version number	2018
Es reference	ES12a

1. Title of exposure scenario

Main title	Use as a Fuel - Industrial
Process scope	Covers the use as a fuel (or fuel additive) and includes activities associated with its transfer, use, equipment maintenance and handling of waste.
Sector of use	NA
<u>Environment</u>	
Environmental release category	ERC7 Use of functional fluid at industrial site
SPERC	ESVOC SPERC 7.12a.v1
<u>Worker</u>	
Process category	PROC1 Chemical production or refinery in closed process without likelihood of exposure or processes with equivalent containment conditions PROC2 Chemical production or refinery in closed continuous process with occasional controlled exposure or processes with equivalent containment conditions PROC3 Manufacture or formulation in the chemical industry in closed batch processes with occasional controlled exposure or processes with equivalent containment condition PROC8a Transfer of substance or mixture (charging and discharging) at non-dedicated facilities PROC8b Transfer of substance or mixture (charging and discharging) at dedicated facilities PROC16 Use of fuels

2. Conditions of use affecting exposure (Industrial - Environment 1)

Product characteristics

Substance is complex UVCB. Predominantly hydrophobic.

Amounts used

Fraction of EU tonnage used in region: 0.1
Regional use tonnage: 5.9E+06 tonnes/year
Fraction of Regional tonnage used locally: 2.6E-01
Annual site tonnage: 1.5E+06 tonnes
Maximum daily site tonnage: 5000 tonnes

Frequency and duration of use

Continuous release.
Emission days: 300 days/year

Other given operational conditions affecting environmental exposure

Use as a Fuel - Industrial

Emission factor - air	Release fraction to air from process (initial release prior to RMM): 2.0E-04
Emission factor - water	Release fraction to wastewater from process (initial release prior to RMM): 1.9E-07
Emission factor - soil	Release fraction to soil from process (initial release prior to RMM): 0

Environmental factors not influenced by risk management measures

Dilution	Local freshwater dilution factor: 10 Local marine water dilution factor: 100
-----------------	---

Risk management measures

Good practice	Common practices vary across sites, thus conservative process release estimates used. Risk from environmental exposure is driven by terrestrial secondary poisoning.
STP details	Not applicable as there is no release to wastewater. Estimated substance removal from wastewater via domestic sewage treatment: 94.2% Total efficiency of removal from wastewater after onsite and offsite (domestic treatment plant) RMMs: 94.2% Maximum allowable site tonnage (Msafe), based on release following total wastewater treatment removal: 7.2E+06 kg/day Assumed domestic sewage treatment plant flow (m ³ /day): 2000.

Technical onsite conditions and measures to reduce or limit discharges to air, water and soil

Air	Treat air emission to provide a typical removal efficiency of 95%.
Water	If discharging to domestic sewage treatment plant, no onsite wastewater treatment required. Treat onsite wastewater (prior to receiving water discharge) to provide the required removal efficiency of (%): ≥ 61.1. If discharging to domestic sewage treatment plant, provide the required onsite wastewater removal efficiency of 0.0%.
Soil	Do not apply industrial sludge to natural soils. Sludge should be incinerated, contained or reclaimed.

Conditions and measures related to external treatment of waste for disposal

Waste treatment	Combustion emissions limited by required exhaust emission controls. Combustion emissions considered in regional exposure assessment. External treatment and disposal of waste should comply with applicable local and/or national regulations.
------------------------	--

Conditions and measures related to external recovery of waste

Recovery method	This substance is consumed during use and no waste of the substance is generated.
------------------------	---

2. Conditions of use affecting exposure (Workers - Health 1)

Product characteristics

Physical state	Liquid
Vapour pressure	Vapour pressure < 0.5 kPa at STP.
Concentration details	Covers percentage substance in the product up to 100% (unless stated differently).

Frequency and duration of use

Covers daily exposures up to 8 hours (unless stated differently).

Other given operational conditions affecting workers exposure

Setting	Assumes a good basic standard of occupational hygiene is implemented.
Temperature	Assumes use at not more than 20°C above ambient temperature, unless stated differently.

Use as a Fuel - Industrial

Organisational measures to prevent/limit releases, dispersion and exposure

Organisational measures General measures (carcinogens) Consider technical advances and process upgrades (including automation) for the elimination of releases. minimise exposure using measures such as closed systems, dedicated facilities and suitable general/local exhaust ventilation. Drain down systems and clear transfer lines prior to breaking containment. Clean/flush equipment, where possible, prior to maintenance Where there is potential for exposure: restrict access to authorised persons; provide specific activity training to operators to minimise exposures; wear suitable gloves and coveralls to prevent skin contamination; wear respiratory protection when its use is identified for certain contributing scenario; clear up spills immediately and dispose of waste safely. Ensure safe systems of work or equivalent arrangements are in place to manage risks. Regularly inspect, test and maintain all control measures. Consider the need for risk based health surveillance.

Risk management measures

Use as a Fuel - Industrial

General exposures (closed systems)

Handle substance within a closed system.

Sample via a closed loop or other system to avoid exposure.

Avoid carrying out activities involving exposure for more than 4 hours.

Wear chemically-resistant gloves (tested to EN374) in combination with 'basic' employee training.

.

General exposures (closed systems)

Product sampling

Handle substance within a closed system.

Sample via a closed loop or other system to avoid exposure.

Avoid carrying out activities involving exposure for more than 1 hour.

Provide a good standard of controlled ventilation (10 to 15 air changes per hour).

Wear chemically-resistant gloves (tested to EN374) in combination with 'basic' employee training.

.

Bulk closed unloading

Outdoor.

Transfer via enclosed lines.

Avoid carrying out activities involving exposure for more than 4 hours.

Wear chemically-resistant gloves (tested to EN374) in combination with 'basic' employee training.

.

Drum/batch transfers

Ensure material transfers are under containment or extract ventilation.

, or:

Provide a good standard of general ventilation (not less than 3 to 5 air changes per hour).

Avoid carrying out activities involving exposure for more than 1 hour.

Wear chemically-resistant gloves (tested to EN374) in combination with 'basic' employee training.

.

Operation of solids filtering equipment

Provide a good standard of general ventilation (not less than 3 to 5 air changes per hour).

Avoid carrying out activities involving exposure for more than 4 hours.

Wear chemically-resistant gloves (tested to EN374) in combination with 'basic' employee training.

.

Bulk product storage

Store substance within a closed system.

Provide a good standard of general ventilation (not less than 3 to 5 air changes per hour).

Avoid carrying out activities involving exposure for more than 4 hours.

Wear chemically-resistant gloves (tested to EN374) in combination with 'basic' employee training.

.

Use as a fuel

(closed systems)

Wear chemically-resistant gloves (tested to EN374) in combination with 'basic' employee training.

.

Equipment cleaning and maintenance

Drain down and flush system prior to equipment break-in or maintenance.

Wear chemically-resistant gloves (tested to EN374) in combination with specific activity training.

Retain drain-downs in sealed storage pending disposal or for subsequent recycle.

Use as a Fuel - Industrial

3. Exposure estimation (Environment 1)

Assessment method	Used Petrorisk model. (Hydrocarbon Block Method)
	Maximum Risk Characterisation Ratios for air emissions 6.9E-01
	Maximum Risk Characterisation Ratios for wastewater emissions 1.5E-01

4. Guidance to check compliance with the exposure scenario (Environment 1)

Guidance is based on assumed operating conditions which may not be applicable to all sites, thus, scaling may be necessary to define appropriate site-specific risk management measures. Required removal efficiency for wastewater can be achieved using onsite/offsite technologies, either alone or in combination. Required removal efficiency for air can be achieved using onsite technologies, either alone or in combination. Further details on scaling and control technologies are provided in SpERC factsheet (<http://cefic.org/en/reach-for-industries-libraries.html>).

3. Exposure estimation (Health 1)

Assessment method	The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise indicated
	Available hazard data do not enable the derivation of a DNEL for carcinogenic effects.
	Available hazard data do not support the need for a DNEL to be established for other health effects. Qualitative approach used to conclude safe use.

4. Guidance to check compliance with the exposure scenario (Health 1)

Predicted exposures are not expected to exceed the DN(M)EL when the Risk Management Measures/Operational Conditions outlined in Section 2 are implemented. Where other Risk Management Measures/Operational Conditions are adopted, then users should ensure that risks are managed to at least equivalent levels.

Exposure scenario

Use as a Fuel - Professional

Identification

Product name	Fuel oil, residual
CAS number	68476-33-5
EC number	270-675-6
Version number	2018
Es reference	ES12b

1. Title of exposure scenario

Main title	Use as a Fuel - Professional
Process scope	Covers the use as a fuel (or fuel additive) and includes activities associated with its transfer, use, equipment maintenance and handling of waste.
Sector of use	NA
<u>Environment</u>	
Environmental release category	ERC9a Widespread use of functional fluid (indoor) ERC9b Widespread use of functional fluid (outdoor)
SPERC	ESVOC SPERC 9.12b.v1
<u>Worker</u>	
Process category	PROC1 Chemical production or refinery in closed process without likelihood of exposure or processes with equivalent containment conditions PROC2 Chemical production or refinery in closed continuous process with occasional controlled exposure or processes with equivalent containment conditions PROC3 Manufacture or formulation in the chemical industry in closed batch processes with occasional controlled exposure or processes with equivalent containment condition PROC8a Transfer of substance or mixture (charging and discharging) at non-dedicated facilities PROC8b Transfer of substance or mixture (charging and discharging) at dedicated facilities PROC16 Use of fuels

2. Conditions of use affecting exposure (Industrial - Environment 1)

Product characteristics

Substance is complex UVCB. Predominantly hydrophobic.

Amounts used

Fraction of EU tonnage used in region: 0.1
Regional use tonnage: 1.7E+06 tonnes/year
Fraction of Regional tonnage used locally: 5.0E-04
Annual site tonnage: 8.5E+02 tonnes
Maximum daily site tonnage: 2.3E+03 kg

Frequency and duration of use

Continuous release.
Emission days: 365 days/year

Other given operational conditions affecting environmental exposure

Use as a Fuel - Professional

Emission factor - air	Release fraction to air from wide dispersive use (regional only): 1.0E-04
Emission factor - water	Release fraction to wastewater from wide dispersive use: 7.0E-10
Emission factor - soil	Release fraction to soil from wide dispersive use (regional only): 0.00001

Environmental factors not influenced by risk management measures

Dilution	Local freshwater dilution factor: 10 Local marine water dilution factor: 100
-----------------	---

Risk management measures

Good practice	Common practices vary across sites, thus conservative process release estimates used. Risk from environmental exposure is driven by humans via indirect exposure (primarily ingestion).
----------------------	--

STP details	Not applicable as there is no release to wastewater. Estimated substance removal from wastewater via domestic sewage treatment: 94.2% Total efficiency of removal from wastewater after onsite and offsite (domestic treatment plant) RMMs: 94.2.% Maximum allowable site tonnage (Msafe), based on release following total wastewater treatment removal: 3.8E+03 kg/day Assumed domestic sewage treatment plant flow (m ³ /day): 2000.
--------------------	--

Technical onsite conditions and measures to reduce or limit discharges to air, water and soil

Air	Treat air emission to provide a typical removal efficiency of N/A%.
Water	No wastewater treatment required. Treat onsite wastewater (prior to receiving water discharge) to provide the required removal efficiency of (%): ≥ 0.0 . If discharging to domestic sewage treatment plant, provide the required onsite wastewater removal efficiency of 0.0%.
Soil	Do not apply industrial sludge to natural soils. Sludge should be incinerated, contained or reclaimed.

Conditions and measures related to external treatment of waste for disposal

Waste treatment	Combustion emissions limited by required exhaust emission controls. Combustion emissions considered in regional exposure assessment. External treatment and disposal of waste should comply with applicable local and/or national regulations.
------------------------	--

Conditions and measures related to external recovery of waste

Recovery method	This substance is consumed during use and no waste of the substance is generated.
------------------------	---

2. Conditions of use affecting exposure (Workers - Health 1)

Product characteristics

Physical state	Liquid
Vapour pressure	Vapour pressure < 0.5 kPa at STP.
Concentration details	Covers percentage substance in the product up to 100% (unless stated differently).

Frequency and duration of use

Covers daily exposures up to 8 hours (unless stated differently).

Other given operational conditions affecting workers exposure

Setting	Assumes a good basic standard of occupational hygiene is implemented.
Temperature	Assumes use at not more than 20°C above ambient temperature, unless stated differently.

Use as a Fuel - Professional

Organisational measures to prevent/limit releases, dispersion and exposure

Organisational measures General measures (carcinogens) Consider technical advances and process upgrades (including automation) for the elimination of releases. minimise exposure using measures such as closed systems, dedicated facilities and suitable general/local exhaust ventilation. Drain down systems and clear transfer lines prior to breaking containment. Clean/flush equipment, where possible, prior to maintenance Where there is potential for exposure: restrict access to authorised persons; provide specific activity training to operators to minimise exposures; wear suitable gloves and coveralls to prevent skin contamination; wear respiratory protection when its use is identified for certain contributing scenario; clear up spills immediately and dispose of waste safely. Ensure safe systems of work or equivalent arrangements are in place to manage risks. Regularly inspect, test and maintain all control measures. Consider the need for risk based health surveillance.

Risk management measures

Use as a Fuel - Professional

General exposures (closed systems)

Product sampling

Handle substance within a closed system.

Sample via a closed loop or other system to avoid exposure.

Avoid carrying out activities involving exposure for more than 1 hour.

Provide a good standard of controlled ventilation (10 to 15 air changes per hour).

Wear chemically-resistant gloves (tested to EN374) in combination with specific activity training.

.

General exposures (closed systems)

Handle substance within a closed system.

Sample via a closed loop or other system to avoid exposure.

Avoid carrying out activities involving exposure for more than 1 hour.

Provide a good standard of controlled ventilation (10 to 15 air changes per hour).

Wear chemically-resistant gloves (tested to EN374) in combination with 'basic' employee training.

.

Bulk closed unloading

Provide a good standard of controlled ventilation (10 to 15 air changes per hour).

Wear chemically-resistant gloves (tested to EN374) in combination with 'basic' employee training.

Avoid carrying out activities involving exposure for more than 1 hour.

, or:

Ensure material transfers are under containment or extract ventilation.

.

Drum/batch transfers

Provide a good standard of controlled ventilation (10 to 15 air changes per hour).

Wear chemically-resistant gloves (tested to EN374) in combination with 'basic' employee training.

Avoid carrying out activities involving exposure for more than 1 hour.

, or:

Ensure material transfers are under containment or extract ventilation.

.

Refuelling

Ensure material transfers are under containment or extract ventilation.

Wear chemically-resistant gloves (tested to EN374) in combination with 'basic' employee training.

Avoid carrying out activities involving exposure for more than 1 hour.

.

Use as a fuel

(closed systems)

Wear chemically-resistant gloves (tested to EN374) in combination with 'basic' employee training.

.

Equipment cleaning and maintenance

Provide a good standard of general ventilation (not less than 3 to 5 air changes per hour).

Wear chemically-resistant gloves (tested to EN374) in combination with specific activity training.

Drain down and flush system prior to equipment break-in or maintenance.

Retain drain-downs in sealed storage pending disposal or for subsequent recycle.

Clear spills immediately.

Use as a Fuel - Professional

Assessment method	Used Petrorisk model. (Hydrocarbon Block Method)
	Maximum Risk Characterisation Ratios for air emissions 5.6E-01
	Maximum Risk Characterisation Ratios for wastewater emissions 3.2E-03

4. Guidance to check compliance with the exposure scenario (Environment 1)

Guidance is based on assumed operating conditions which may not be applicable to all sites, thus, scaling may be necessary to define appropriate site-specific risk management measures. Required removal efficiency for wastewater can be achieved using onsite/offsite technologies, either alone or in combination. Required removal efficiency for air can be achieved using onsite technologies, either alone or in combination. Further details on scaling and control technologies are provided in SpERC factsheet (<http://cefic.org/en/reach-for-industries-libraries.html>).

3. Exposure estimation (Health 1)

Assessment method	The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise indicated
	Available hazard data do not enable the derivation of a DNEL for carcinogenic effects. Available hazard data do not support the need for a DNEL to be established for other health effects. Qualitative approach used to conclude safe use.

4. Guidance to check compliance with the exposure scenario (Health 1)

Predicted exposures are not expected to exceed the DN(M)EL when the Risk Management Measures/Operational Conditions outlined in Section 2 are implemented. Where other Risk Management Measures/Operational Conditions are adopted, then users should ensure that risks are managed to at least equivalent levels.