

Supersedes date
12/07/2023

Revision date
20/06/2024

Revision Number
2
Country-Language: FIN-EN

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product Name JET A-1 containing Neste MY Sustainable Aviation Fuel

Product Code(s) 15843

Unique Formula Identifier (UFI) UFI: 96VD-G1GM-C004-NQ0D

Pure substance/mixture Mixture

Contains Renewable hydrocarbons (kerosine type fraction), Distillates (petroleum), light hydrocracked, Kerosine (petroleum), hydrodesulfurized, Distillates (petroleum), hydrotreated light, Kerosine (petroleum), Kerosine (petroleum), sweetened

1.2. Relevant identified uses of the substance or mixture and uses advised against

Recommended use Use as a fuel (ES012a, ES012b)

Uses advised against Supported uses are listed above. Other uses are not recommended.

1.3. Details of the supplier of the safety data sheet

Supplier

Neste Components B.V.
Mercuriusplein 1, 2132 HA Hoofddorp, The Netherlands
sds@neste.com (chemical safety)

1.4. Emergency telephone number

Emergency Telephone :

Emergency Telephone - §45 - (EC)1272/2008	
Europe	112
Austria	Chemwatch Austria: +43 800 281336
Croatia	+3851 2348 342
Cyprus	1401 (ώρες λειτουργίας 24 ώρες/24ωρο, 7 ημέρες την εβδομάδα)
Czech Republic	Toxikologické informační středisko: +420 224 919 293, +420 224 915 402
Denmark	Gifflinjen: +45 8212 1212
Estonia	Poison information telephone number: 16662, calling from abroad: (+372) 7943 794
Finland	+358 800 147 111, +358 9 471 977, Poison Information Centre
France	France: Numéro ORFILA (INRS) : + 33 (0)1 45 42 59 59.
Germany	+49 32 211121704, Chemwatch Emergency Response Phone Number
Greece	(0030) 2107793777 (ώρες λειτουργίας 24 ώρες/24ωρο, 7 ημέρες την εβδομάδα)
Iceland	Phone: 543 2222. The poison center is open 24 hours a day.
Ireland	(01) 809 2166
Latvia	Valsts toksikoloģijas centrs: (+371) 6704 2473
Lithuania	Neatidėliotina informacija apsinuodijus: +370 5 236 20 52.
Netherlands	NVIC (088 755 8000), Only for the purpose of informing medical personnel in case of acute intoxications.

Norway	Poison Information Centre +47 22 59 13 00.
Poland	+48 22 208 6439, Chemwatch Emergency Response Telephone Number
Portugal	Em caso de intoxicação, ligue +351 800 250 250. (Centro de Informação Antivenenos (CIAV))
Romania	Centrul de Informare Toxicologie de la Spitalul Clinic de Urgență București: +40215992300
Slovakia	Národné toxikologické informačné centrum: +421 2 5477 4166
Slovenia	112
Spain	+34 91 562 04 20 (24h/7)
Sweden	När det är akut: 112, begär giftinformation. I mindre akuta fall 010-456 6700, Giftinformationscentralens direktnummer

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Regulation (EC) No 1272/2008

Flammable liquids	Category 3 - (H226)
Acute toxicity - Inhalation (Gases)	Category 4 - (H332)
Acute toxicity - Inhalation (Vapours)	Category 4 - (H332)
Acute toxicity - Inhalation (Dusts/Mists)	Category 4 - (H332)
Skin corrosion/irritation	Category 2 - (H315)
Carcinogenicity	Category 1B - (H350)
Specific target organ toxicity — single exposure	Category 3 - (H336)
Category 3 Narcotic effects	
Specific target organ toxicity — repeated exposure	Category 2 - (H373)
Aspiration hazard	Category 1 - (H304)
Chronic aquatic toxicity	Category 2 - (H411)

2.2. Label elements

Contains Renewable hydrocarbons (kerosine type fraction), Distillates (petroleum), light hydrocracked, Kerosine (petroleum), hydrodesulfurized, Distillates (petroleum), hydrotreated light, Kerosine (petroleum), Kerosine (petroleum), sweetened



Signal word

Danger

Hazard statements

H226 - Flammable liquid and vapour

H304 - May be fatal if swallowed and enters airways

H315 - Causes skin irritation

H332 - Harmful if inhaled

H336 - May cause drowsiness or dizziness

H350 - May cause cancer

H373 - May cause damage to organs through prolonged or repeated exposure

H411 - Toxic to aquatic life with long lasting effects

Precautionary Statements - EU (§28, 1272/2008)

P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking

P260 - Do not breathe fumes

P273 - Avoid release to the environment

P280 - Wear protective gloves/protective clothing/eye protection/face protection

P301 + P310 - IF SWALLOWED: Immediately call a POISON CENTER or doctor
 P331 - Do NOT induce vomiting

2.3. Other hazards

Evaporates slowly. Contact with eyes may cause irritation.
 Risk of soil and ground water contamination.

This product does not contain substances considered to have endocrine disrupting properties at levels of 0.1% or higher.

SECTION 3: Composition/information on ingredients

3.1 Substances

Not applicable

3.2 Mixtures

Chemical name	Weight-%	REACH registration number	EC No (EU Index No)	Classification according to Regulation (EC) No. 1272/2008 [CLP]	Specific concentration limit (SCL)	M-Factor	M-Factor (long-term)
Renewable hydrocarbons (kerosine type fraction)	<= 50%	01-2119850115-46-0000/0001/0003	931-082-4	Flam. Liq. 3 (H226) Asp. Tox. 1 (H304)	-	-	-
Distillates (petroleum), light hydrocracked 64741-77-1	0 - =>50%*	01-2119474208-35	265-078-2	Asp. Tox. 1 (H304) Skin Irrit. 2 (H315) Acute Tox. 4 (H332) Carc. 2 (H351) STOT RE 2 (H373) Aq. Chronic 2 (H411)	-	-	-
Kerosine (petroleum), hydrodesulfurized 64742-81-0	0 - =>50%*	01-2119462828-25	265-184-9	Flam. Liq. 3 (H226) Asp. Tox. 1 (H304) Skin Irrit. 2 (H315) STOT SE 3 (H336) Aq. Chronic 2 (H411)	-	-	-
Kerosine (petroleum), sweetened 91770-15-9	0 - =>50%*	01-2119502385-46	294-799-5	Flam. Liq. 3 (H226) Asp. Tox. 1 (H304) Skin Irrit. 2 (H315) STOT SE 3 (H336) Aq. Chronic 2 (H411)	-	-	-
Kerosine (petroleum) 8008-20-6	0 - =>50%*	01-2119485517-27	232-366-4	Flam. Liq. 3 (H226) Asp. Tox. 1 (H304) Skin Irrit. 2 (H315) STOT SE 3 (H336) Aq. Chronic 2 (H411)	-	-	-
Distillates (petroleum), hydrotreated light 64742-47-8	0 - =>50%*	01-2119484819-18	265-149-8	Flam. Liq. 3 (H226) Asp. Tox. 1 (H304) Skin Irrit. 2 (H315) STOT SE 3 (H336) Aq. Chronic 2 (H411)	-	-	-

Full text of H- and EUH-phrases: see section 16

This product does not contain candidate substances of very high concern at a concentration $\geq 0.1\%$ (Regulation (EC) No. 1907/2006 (REACH), Article 59)

Additional information

Mixture of renewable raw material fuel, petroleum product and additives. * Total content of fossil components $\geq 50\%$. Total aromatics at maximum: 13,5 %. Naphthalene (CAS 91-20-3) < 1%. Toluene (CAS 108-88-3) < 1%. Benzene (CAS 71-43-2) < 0,1 %.

NOTE: One or more of the fossil components may contain more than 0.1% cumene (CAS 98-82-8), a class 1B (H350) carcinogen.

Renewable hydrocarbons (kerosine type fraction): Identity outside the EU (CAS number and name of the substance) Alkanes, C8-18- branched and linear (CAS 2252265-89-5)

SECTION 4: First aid measures

4.1. Description of first aid measures

General advice	Show this safety data sheet to the doctor in attendance.
Inhalation	P340 - Remove victim to fresh air and keep at rest in a position comfortable for breathing. If breathing is difficult, (trained personnel should) give oxygen. Get medical attention immediately if symptoms occur.
Eye contact	Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention if irritation develops and persists.
Skin contact	Wash off immediately with soap and plenty of water. In the case of skin irritation or allergic reactions see a doctor.
Ingestion	ASPIRATION HAZARD IF SWALLOWED - CAN ENTER LUNGS AND CAUSE DAMAGE. Do NOT induce vomiting. If vomiting occurs spontaneously, keep head below hips to prevent aspiration. Never give anything by mouth to an unconscious person. Get immediate medical attention.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms	May irritate eyes and skin. Vapours in high concentrations are narcotic. May cause nausea, headache, dizziness and intoxication. Entry into the lungs following ingestion or vomiting may cause chemical pneumonitis.
-----------------	---

4.3. Indication of any immediate medical attention and special treatment needed

Note to doctors	Treat symptomatically.
------------------------	------------------------

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable Extinguishing Media	Dry chemical. Carbon dioxide (CO2). Water spray. Alcohol resistant foam.
Large Fire	CAUTION: Use of water spray when fighting fire may be inefficient.
Unsuitable extinguishing media	Do not scatter spilled material with high pressure water streams.

5.2. Special hazards arising from the substance or mixture

Specific hazards arising from the chemical Flammable liquid and vapour. Containers may explode when heated.

Hazardous combustion products Carbon dioxide (CO₂). Carbon monoxide.

5.3. Advice for firefighters

Special protective equipment and precautions for fire-fighters Cool containers exposed to heat with water spray and remove them from the fire area if it can be done without risk. Prevent fire extinguishing water from contaminating surface water or the ground water system.

Wear positive pressure self-contained breathing apparatus (SCBA).

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions Ensure adequate ventilation. Do not breathe vapour or mist. Avoid contact with skin, eyes or clothing. Use personal protective equipment as required.

For emergency responders Prevent unauthorized access. Keep people away from and upwind of spill/leak.

Vapours may accumulate in confined areas (basement, tanks, hopper/tank cars, etc.).
ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area).
Take precautionary measures against static discharges.

6.2. Environmental precautions

Environmental precautions Avoid release to the environment. Prevent further leakage or spillage if safe to do so. Inform the relevant authorities if environmental pollution occurs (sewers, waterways, soil or air).
Risk of soil and ground water contamination.

6.3. Methods and material for containment and cleaning up

Methods for containment Stop leak if you can do it without risk. Keep out of drains, sewers, ditches and waterways.

Methods for cleaning up Immediately start clean-up of the liquid and contaminated soil. Take up with sand, earth or other non-combustible absorbent material. Keep in suitable, closed containers for disposal. Large spills should be collected mechanically (remove by pumping) for disposal. Pay attention to the fire and health hazards caused by the product.

Prevention of secondary hazards Clean contaminated objects and areas thoroughly observing environmental regulations.

6.4. Reference to other sections

Reference to other sections See Section 7, 8, 13 for more information.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling The product contains volatile substances which may spread in the atmosphere. Keep away from open flames, hot surfaces and sources of ignition. Take precautionary measures

against static discharges. Ground and bond all lines and equipment associated with product system. All equipment should be non-sparking and explosion proof.

Use only outdoors or in a well-ventilated area. Try to avoid product volatilization during handling and transferring. Avoid breathing vapours or mists. Avoid contact with skin, eyes or clothing. Use personal protective equipment and/or local ventilation when needed. During tank operations follow special instructions (risk of oxygen displacement and hydrocarbons).

General hygiene considerations Handle in accordance with good industrial hygiene and safety practice. Do not eat, drink or smoke when using this product. Wash hands before breaks and immediately after handling the product. Clear up spills immediately and dispose of waste safely.

7.2. Conditions for safe storage, including any incompatibilities

Storage Conditions Flammable liquid storage. Store in accordance with local regulations. Keep in properly labelled containers. Keep containers tightly closed in a dry, cool and well-ventilated place. Protect from direct sunlight. Store in a demarcated bunded area to prevent release to drains and/or watercourses.

7.3. Specific end use(s)

Risk Management Methods (RMM) Not applicable.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Exposure Limits Naphthalene: 10 ppm (8h), 50 mg/m³ (8h), EU OELV (EC/1991/322).
 Naphthalene: 1 ppm (8h), 5 mg/m³ (8h), 2 ppm (15min), 10mg/m³ (15min), HTP 2020/FIN. (skin).
 Cumene: 10 ppm (8h), 50 mg/m³ (8h), 50 ppm (15 min), 250 mg/m³ (15min), EU OELV (EC 2019/1831), HTP 2020/FIN (skin).

Kerosine as total hydrocarbon vapor; ACGIH TLV®-TWA (8h) 200 mg/m³ (non-aerosol).

Chemical name	European Union	Austria	Belgium	Bulgaria	Croatia
Kerosine (petroleum) 8008-20-6	-	-	TWA: 200 mg/m ³ D*	TWA: 300.0 mg/m ³	-
Chemical name	Cyprus	Czech Republic	Denmark	Estonia	Finland
Kerosine (petroleum) 8008-20-6	-	-	-	TWA: 5 mg/kg STEL: 500 mg/m ³	-
Distillates (petroleum), hydrotreated light 64742-47-8	-	-	-	TWA: 5 mg/kg STEL: 500 mg/m ³	-
Chemical name	France	Germany TRGS	Germany DFG	Greece	Hungary
Kerosine (petroleum) 8008-20-6	-	TWA:	TWA: 5 mg/m ³ TWA: 50 ppm TWA: 350 mg/m ³ Peak: 20 mg/m ³ Peak: 100 ppm Peak: 700 mg/m ³	-	-
Distillates (petroleum), hydrotreated light 64742-47-8	-	TWA:	TWA: 5 mg/m ³ TWA: 50 ppm TWA: 350 mg/m ³	-	-

			Peak: 20 mg/m ³ Peak: 100 ppm Peak: 700 mg/m ³		
Chemical name	Ireland	Italy MDLPS	Italy AIDII	Latvia	Lithuania
Kerosine (petroleum), hydrodesulfurized 64742-81-0	-	-	TWA: 200 mg/m ³ cute*	-	-
Kerosine (petroleum) 8008-20-6	Sk*	-	TWA: 200 mg/m ³ cute*	-	-
Chemical name	Luxembourg	Malta	Netherlands	Norway	Poland
Kerosine (petroleum) 8008-20-6	-	-	-	-	STEL: 300 mg/m ³ TWA: 100 mg/m ³
Chemical name	Portugal	Romania	Slovakia	Slovenia	Spain
Kerosine (petroleum), hydrodesulfurized 64742-81-0	TWA: 200 ppm Cutânea*	-	-	-	-
Kerosine (petroleum) 8008-20-6	TWA: 200 ppm Cutânea*	-	-	-	TWA: 200 mg/m ³ vía dérmica*
Chemical name	Sweden		Switzerland		United Kingdom
Kerosine (petroleum) 8008-20-6	-		TWA: 50 ppm TWA: 350 mg/m ³ TWA: 5 mg/m ³ STEL: 20 mg/m ³ STEL: 100 ppm STEL: 700 mg/m ³		-
Distillates (petroleum), hydrotreated light 64742-47-8	-		TWA: 50 ppm TWA: 350 mg/m ³ TWA: 5 mg/m ³ STEL: 100 ppm STEL: 700 mg/m ³		-

Derived No Effect Level (DNEL) - Workers

Chemical name	Oral	Dermal	Inhalation
Renewable hydrocarbons (kerosine type fraction) -	-	42 mg/kg/day [4] [6]	147 mg/m ³ [4] [6]
Distillates (petroleum), light hydrocracked 64741-77-1	-	2.91 mg/kg bw/day [4] [6]	68.34 mg/m ³ [4] [6] 4288 mg/m ³ [4] [7]
Kerosine (petroleum), hydrodesulfurized 64742-81-0	-	7.7 mg/kg bw/day [4] [6]	50 mg/m ³ [4] [6] 250 mg/m ³ [5] [7]

Derived No Effect Level (DNEL) - General Public

Chemical name	Oral	Dermal	Inhalation
Distillates (petroleum), light hydrocracked 64741-77-1	1.25 mg/kg bw/day [4] [6]	1.25 mg/kg bw/day [4] [6]	20.22 mg/m ³ [4] [6] 2572.8 mg/m ³ [4] [7]
Kerosine (petroleum), hydrodesulfurized 64742-81-0	5 mg/kg bw/day [4] [6]	1.64 mg/kg bw/day [4] [6]	10.66 mg/m ³ [4] [6]

Chemical name	Oral	Dermal	Inhalation
Distillates (petroleum), hydrotreated light 64742-47-8	18.75 mg/kg bw/day [4] [6]	-	-

- [4] Systemic health effects.
- [5] Local health effects.
- [6] Long term.
- [7] Short term.

Predicted No Effect Concentration (PNEC) No information available.

8.2. Exposure controls

Engineering controls Use only in well-ventilated areas. Use personal protective equipment and/or local ventilation when needed. During tank operations follow special instructions (risk of oxygen displacement and hydrocarbons).

Personal protective equipment

Eye/face protection Wear safety glasses with side shields (or goggles).

Hand protection Wear protective gloves. It is recommended that gloves are made of the following material: Nitrile rubber. Neoprene. Polyvinyl chloride (PVC). Wear suitable gloves tested to EN 374. Change protective gloves regularly. Ensure that the breakthrough time of the glove material is not exceeded. Refer to glove supplier for information on breakthrough time for specific gloves.

Skin and body protection Wear suitable protective clothing. Wear anti-static protective clothing if there is a risk of ignition from static electricity.

Respiratory protection Respiratory protection must be used if the airborne contamination exceeds the recommended occupational exposure limit. Wear a respirator fitted with the following cartridge: Gas filter. A2. Filter must be changed often enough. Gas and combination filter cartridges must comply with EN 14387.

General hygiene considerations Handle in accordance with good industrial hygiene and safety practice. Do not eat, drink or smoke when using this product. Wash hands before breaks and immediately after handling the product. Clear up spills immediately and dispose of waste safely.

Environmental exposure controls Store in a demarcated bunded area to prevent release to drains and/or watercourses.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state Liquid
Colour clear
Odour Hydrocarbons.
Odour threshold -

<u>Property</u>	<u>Values</u>	<u>Remarks • Method</u>
Melting point / freezing point	< -47 °C	
Initial boiling point and boiling range	115 - 300 °C	(ASTM D 86)

Flammability	H226	-
Flammability Limit in Air		-
Upper flammability or explosive limits	6 %	
Lower flammability or explosive limits	0,6 %	
Flash point	≥ 38 °C	(IP 170)
Autoignition temperature	207 - 250°C	(EN 14522)
Decomposition temperature	-	-
pH	No data available	Not applicable
pH (as aqueous solution)	No data available	
Kinematic viscosity	< 7 mm ² /s @ 40 °C	EN ISO 3104
Dynamic viscosity	< 4 mPa s @ 20°C	EN ISO 3104
Water solubility	< 50 mg/L @ 20 °C	The product has poor water-solubility.
Solubility(ies)	-	-
Partition coefficient	-	No data available
Vapour pressure	~ 2 kPa @ 38°C	-
Relative density	0,78 - 0,84 @ 15 °C	-
Bulk density	-	
Liquid Density	-	
Relative vapour density	> 3	. (air = 1)
Particle characteristics		Not applicable
Particle Size	n/a	
Particle Size Distribution	n/a	

9.2. Other information

9.2.1. Information with regards to physical hazard classes

Explosive properties	Not considered to be explosive
Oxidising properties	Does not meet the criteria for classification as oxidising

9.2.2. Other safety characteristics

No information available

SECTION 10: Stability and reactivity

10.1. Reactivity

Reactivity	There are no known reactivity hazards associated with this product.
-------------------	---

10.2. Chemical stability

Stability	Stable under normal conditions.
------------------	---------------------------------

Sensitivity to static discharge	Yes.
--	------

10.3. Possibility of hazardous reactions

Possibility of hazardous reactions	None known.
---	-------------

10.4. Conditions to avoid

Conditions to avoid	Keep away from heat, sparks and open flame.
----------------------------	---

10.5. Incompatible materials

Incompatible materials	Oxidising agent.
-------------------------------	------------------

10.6. Hazardous decomposition products

Hazardous decomposition products None under normal use conditions.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Information on likely routes of exposure

Acute toxicity Harmful if inhaled

Numerical measures of toxicity

Chemical name	Oral LD50	Dermal LD50	Inhalation LC50
Renewable hydrocarbons (kerosine type fraction)	> 2000 mg/kg, Rat (EC B1 tris)	> 2000 mg/kg, Rat (EC B3)	-
Distillates (petroleum), light hydrocracked	> 5000 mg/kg (Rat)	> 4300 mg/kg (Rabbit)	= 4.1 mg/L (Rat) 4 h
Kerosine (petroleum), hydrodesulfurized	> 5000 mg/kg (Rat)	> 2000 mg/kg (Rabbit)	> 5200 mg/m ³ (Rat) 4 h
Kerosine (petroleum), sweetened	> 5000 mg/kg (Rat)	> 2000 mg/kg (Rabbit)	> 5.2 mg/L (Rat) 4 h
Kerosine (petroleum)	> 5000 mg/kg (Rat)	> 2000 mg/kg (Rabbit)	> 5.28 mg/L (Rat) 4 h
Distillates (petroleum), hydrotreated light	> 5000 mg/kg (Rat)	> 2000 mg/kg (Rabbit)	> 5.2 mg/L (Rat) 4 h

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Skin corrosion/irritation	May cause skin irritation.
Serious eye damage/eye irritation	May cause eye and respiratory irritation. Based on available data, the classification criteria are not met.
Respiratory or skin sensitisation	Based on available data, the classification criteria are not met.
Germ cell mutagenicity	Based on available data, the classification criteria are not met.
Carcinogenicity	May cause cancer.
Reproductive toxicity	Based on available data, the classification criteria are not met.

STOT - single exposure May cause drowsiness or dizziness.

STOT - repeated exposure May cause damage to organs through prolonged or repeated exposure.

Aspiration hazard May be fatal if swallowed and enters airways. Entry into the lungs following ingestion or vomiting may cause chemical pneumonitis.

11.2. Information on other hazards

11.2.1. Endocrine disrupting properties

Endocrine disrupting properties This product does not contain substances considered to have endocrine disrupting properties at levels of 0.1% or higher.

11.2.2. Other information

Other adverse effects No information available.

SECTION 12: Ecological information

12.1. Toxicity

Ecotoxicity Toxic to aquatic life with long lasting effects.

Chemical name	Algae/aquatic plants	Fish	Toxicity to microorganisms	Crustacea
Renewable hydrocarbons (kerosine type fraction)	EL50, 72 h: > 100 mg/l, WAF (OECD 201)	LL50, 96 h: > 1000 mg/l, WAF (OECD 203)	EC50, 3 h: > 1000 mg/l, Micro-organisms (wastewater sludge)(OECD 209)	EL50, 48 h: > 100 mg/l, WAF (OECD 202) NOEC, 21 d: 1 mg/l, LOEC, 21 d: 3,2 mg/l, Daphnia magna WAF (OECD 211) NOEC, 10 d: 373 mg/kg, LC50, 10 d: 1200 mg/kg, Sediment organisms (OSPAR Protocols, Part A: Sediment Bioassay, 2005)
Distillates (petroleum), light hydrocracked	ErL50, 72 h: 22 mg/L	LL50, 96 h: =21 mg/L	-	EL50, 48 h:68 mg/L, Daphnia magna
Kerosine (petroleum), hydrodesulfurized	EL50, 72 h: 1-3 mg/L, Raphidocelis subcapitata (OECD 201)	LL50, 96 h: 2-5 mg/L, Oncorhynchus mykiss (OECD 203)	-	EL50, 48 h: =1.4 mg/L, Daphnia magna (OECD 202) EL50, 21 d: =0.89 mg/L, Daphnia magna (OECD 211)
Kerosine (petroleum), sweetened	-	LC50: =45mg/L (96h, Pimephales promelas) LC50: =1740mg/L (96h, Lepomis macrochirus)	-	LC50: =4720mg/L (48h, Den-dronereides heteropoda)
Distillates (petroleum), hydrotreated light	-	LC50: =45mg/L (96h, Pimephales promelas)	-	-

		LC50: =2.2mg/L (96h, Lepomis macrochirus) LC50: =2.4mg/L (96h, Oncorhynchus mykiss)		
--	--	--	--	--

12.2. Persistence and degradability

Persistence and degradability Inherently biodegradable.

The product contains volatile substances which may spread in the atmosphere. Can be photodegraded in the atmosphere.

Renewable hydrocarbons (kerosine type fraction) (-)

Method	Exposure time	Value	Results
OECD Test No. 301B: Ready Biodegradability: CO2 Evolution Test (TG 301 B)			Readily biodegradable

12.3. Bioaccumulative potential

Bioaccumulation Possibly bioaccumulative.

12.4. Mobility in soil

Mobility in soil Evaporates slowly. The product has poor water-solubility. Product can penetrate soil until reaching the surface of ground water. The product contains substances which are bound to particulate matter and are retained in soil.

12.5. Results of PBT and vPvB assessment

PBT and vPvB assessment This mixture contains no substance considered to be persistent, bioaccumulating or toxic (PBT). This mixture contains no substance considered to be very persistent nor very bioaccumulating (vPvB).

12.6. Endocrine disrupting properties

Endocrine disrupting properties This product does not contain substances considered to have endocrine disrupting properties at levels of 0.1% or higher.

12.7. Other adverse effects

Product causes fouling, and direct contact produces harmful effects e.g. to birds and vegetation.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste from residues/unused products Dispose of in accordance with local regulations. When handling waste, the safety precautions applying to handling of the product should be considered. Do not allow into any sewer, on the ground or into any body of water.

Contaminated packaging Care should be taken when handling emptied containers that have not been thoroughly cleaned or rinsed out. Product residues retained in emptied containers can be hazardous.

Waste codes / waste designations Waste codes should be assigned by the user based on the application for which the product

according to EWC was used.
For example: 13 07 03 other fuels (including mixtures).

SECTION 14: Transport information

IATA

14.1 UN number or ID number UN 1863
14.2 UN proper shipping name Fuel, aviation, turbine engine
14.3 Transport hazard class(es) 3
14.4 Packing group III
14.5 Environmental hazards Yes
14.6 Special precautions for user -

IMDG

14.1 UN number or ID number UN 1863
14.2 UN proper shipping name Fuel, aviation, turbine engine
14.3 Transport hazard class(es) 3
14.4 Packing group III
14.5 Environmental hazard Marine pollutant
14.6 Special precautions for user -
14.7 Maritime transport in bulk according to IMO instruments MARPOL Annex I (This cargo is considered an Energy-rich fuel and effective 1 January 2019 should be carried subject to Annex I of MARPOL, see Annex 12 of MEPC.2/Circ.24. Please also refer to MEPC.1/Circ.879 - GUIDELINES FOR THE CARRIAGE OF ENERGY-RICH FUELS AND THEIR BLENDS)

RID

14.1 UN number or ID number UN 1863
14.2 UN proper shipping name Fuel, aviation, turbine engine
14.3 Transport hazard class(es) 3
14.4 Packing group III
14.5 Environmental hazard Yes
14.6 Special precautions for user -

ADR

14.1 UN number or ID number UN 1863
14.2 UN proper shipping name Fuel, aviation, turbine engine
14.3 Transport hazard class(es) 3
14.4 Packing group III
14.5 Environmental hazard Yes
14.6 Special precautions for user
Classification code 30
Tunnel restriction code D/E
-

ADN

UN number or ID number UN 1863
UN proper shipping name Fuel, aviation, turbine engine
Transport hazard class(es) 3
Subsidiary hazard class N2 + CMR
Packing group III

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

National regulations

UK REACH Registration number: UK-01-5174728449-8-XXXX
OR UK: Penman Consulting Limited 42, Aspect House, Waylands Avenue, Grove Business Park, Wantage, Oxon, OX12 9FF, United Kingdom; Telephone: 01367 718474; Email:

pcltd42@penmanconsulting.com.

European Union

Take note of Directive 98/24/EC on the protection of the health and safety of workers from the risks related to chemical agents at work.

Authorisations and/or restrictions on use:

This product does not contain substances subject to authorisation (Regulation (EC) No. 1907/2006 (REACH), Annex XIV)

Persistent Organic Pollutants

Not applicable

Ozone-depleting substances (ODS) regulation (EC) 1005/2009

Not applicable

Other Regulations

Safety Data Sheet according to Regulation (EC) No. 1907/2006 (REACH).
Classification according to Regulation (EC) No. 1272/2008 [CLP].

15.2. Chemical safety assessment

Chemical Safety Report

Chemical Safety Assessments have been carried out for these substances

SECTION 16: Other information

Key or legend to abbreviations and acronyms used in the safety data sheet

Full text of H-Statements referred to under section 3

H226 - Flammable liquid and vapour

H304 - May be fatal if swallowed and enters airways

H315 - Causes skin irritation

H332 - Harmful if inhaled

H336 - May cause drowsiness or dizziness

H350 - May cause cancer

H351 - Suspected of causing cancer

H373 - May cause damage to organs through prolonged or repeated exposure

H411 - Toxic to aquatic life with long lasting effects

Legend

SVHC: Substances of Very High Concern for Authorisation:

Legend Section 8: Exposure controls/personal protection

TWA

TWA (time-weighted average)

STEL

STEL (Short Term Exposure Limit)

Ceiling

Maximum limit value

*

Skin designation

+

Sensitisers

Classification procedure	
Classification according to Regulation (EC) No. 1272/2008 [CLP]	Method Used
Acute oral toxicity	Calculation method
Acute dermal toxicity	Calculation method
Acute inhalation toxicity - gas	Calculation method
Acute inhalation toxicity - vapour	Calculation method
Acute inhalation toxicity - dust/mist	Calculation method
Skin corrosion/irritation	Calculation method
Serious eye damage/eye irritation	Calculation method
Respiratory sensitisation	Calculation method
Skin sensitisation	Calculation method
Mutagenicity	Calculation method
Carcinogenicity	Calculation method
STOT - single exposure	Calculation method
STOT - repeated exposure	Calculation method
Acute aquatic toxicity	Calculation method
Chronic aquatic toxicity	Calculation method
Aspiration hazard	Calculation method
Ozone	Calculation method

Supersedes date 12/07/2023

Revision date 20/06/2024

Reason for revision Updated, sections: 1-3, 8, 11, 14. Change in the mixture classification (new SDS software has been introduced)

Restrictions on use Restricted to professional users

Further information Key literature references and sources for data : Regulations, databases, literature, own research. Chemical Safety Report CONCAWE Report 09/23: Hazard classification and labelling of petroleum substances in the EEA - 2023.

Safety Data Sheet according to Regulation (EC) No. 1907/2006 (REACH)

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

End of Safety Data Sheet

Exposure scenario

Use as a Fuel - Industrial

Identification

Product name	Kerosines
Version number	2018
Es reference	ES12a

1. Title of exposure scenario

Main title	Use as a Fuel - Industrial
Process scope	Covers the use as a fuel (or fuel additive) and includes activities associated with its transfer, use, equipment maintenance and handling of waste.

Environment

Environmental release category
ERC7 Use of functional fluid at industrial site

SPERC
ESVOC SPERC 7.12a.v1

Worker

Process category
PROC1 Chemical production or refinery in closed process without likelihood of exposure or processes with equivalent containment conditions
PROC2 Chemical production or refinery in closed continuous process with occasional controlled exposure or processes with equivalent containment conditions
PROC3 Manufacture or formulation in the chemical industry in closed batch processes with occasional controlled exposure or processes with equivalent containment condition
PROC8a Transfer of substance or mixture (charging and discharging) at non-dedicated facilities
PROC8b Transfer of substance or mixture (charging and discharging) at dedicated facilities
PROC16 Use of fuels

2. Conditions of use affecting exposure (Industrial - Environment 1)

Product characteristics

Substance is complex UVCB. Predominantly hydrophobic.

Amounts used

Fraction of EU tonnage used in region: 0.1
Regional use tonnage: 1,600,000 tonnes/year
Fraction of Regional tonnage used locally: 1
Annual site tonnage: 1,500,000 tonnes
Maximum daily site tonnage: 5000 tonnes

Frequency and duration of use

Continuous release.
Emission days: 300 days/year

Other given operational conditions affecting environmental exposure

Emission factor - air	Release fraction to air from process (initial release prior to RMM): 5.0E-02
Emission factor - water	Release fraction to wastewater from process (initial release prior to RMM): 1.0E-05
Emission factor - soil	Release fraction to soil from process (initial release prior to RMM): 0

Environmental factors not influenced by risk management measures

Use as a Fuel - Industrial

Dilution Local freshwater dilution factor: 10
Local marine water dilution factor: 100

Risk management measures

Good practice Common practices vary across sites, thus conservative process release estimates used.
Risk from environmental exposure is driven by freshwater sediment.

STP type Municipal STP.

STP details Estimated substance removal from wastewater via domestic sewage treatment: 95.0%
Removal efficiency (total): 95%
Maximum allowable site tonnage (M_{safe}), based on release following total wastewater treatment removal: 2.1E+06 tonne/day
Assumed domestic sewage treatment plant flow (m³/day):
2000.

Technical onsite conditions and measures to reduce or limit discharges to air, water and soil

Air Treat air emission to provide a typical removal efficiency of 95%.

Water Prevent leaks and prevent soil/water pollution caused by leaks. Treat onsite wastewater (prior to receiving water discharge) to provide the required removal efficiency of (%): 94.4 If discharging to domestic sewage treatment plant, provide the required onsite wastewater removal efficiency of (%): 0.0

Soil Do not apply industrial sludge to natural soils. Sludge should be incinerated, contained or reclaimed.

Conditions and measures related to external treatment of waste for disposal

Waste treatment Combustion emissions limited by required exhaust emission controls. Combustion emissions considered in regional exposure assessment.

Conditions and measures related to external recovery of waste

Recovery method This substance is consumed during use and no waste of the substance is generated.

2. Conditions of use affecting exposure (Workers - Health 1)

Product characteristics

Physical state Liquid

Vapour pressure Vapour pressure 0.5 - 10 kPa at STP.

Concentration details Covers percentage substance in the product up to 100% (unless stated differently).

Frequency and duration of use

Covers daily exposures up to 8 hours (unless stated differently).

Other given operational conditions affecting workers exposure

Setting Assumes a good basic standard of occupational hygiene is implemented.

Temperature Assumes use at not more than 20°C above ambient temperature, unless stated differently.

Organisational measures to prevent/limit releases, dispersion and exposure

Organisational measures General measures (skin irritants) Avoid direct skin contact with product. Identify potential areas for indirect skin contact. Wear gloves (tested to EN374) if hand contact with substance likely. Clean up contamination/spills as soon as they occur. Wash off any skin contamination immediately. Provide basic employee training to prevent/minimise exposures and to report any skin problems that may develop.

Use as a Fuel - Industrial

Risk management measures

General exposures (closed systems)
No other specific measures identified.

.
Use as a fuel
(closed systems)
No other specific measures identified.

.
Bulk transfers
No other specific measures identified.

.
Drum/batch transfers
No other specific measures identified.

.
Equipment cleaning and maintenance
No other specific measures identified.

.
Bulk product storage
No other specific measures identified.

3. Exposure estimation (Environment 1)

Assessment method	Used Petrorisk model. (Hydrocarbon Block Method)
	Maximum Risk Characterisation Ratios for air emissions 2.9E-02 Maximum Risk Characterisation Ratios for wastewater emissions 9.0E-01

4. Guidance to check compliance with the exposure scenario (Environment 1)

Guidance is based on assumed operating conditions which may not be applicable to all sites, thus, scaling may be necessary to define appropriate site-specific risk management measures. Required removal efficiency for wastewater can be achieved using onsite/offsite technologies, either alone or in combination. Required removal efficiency for air can be achieved using onsite technologies, either alone or in combination. Further details on scaling and control technologies are provided in SpERC factsheet (<http://cefic.org/en/reach-for-industries-libraries.html>).

3. Exposure estimation (Health 1)

Assessment method	The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise indicated
	Available hazard data do not enable the derivation of a DNEL for dermal irritant effects. Qualitative approach used to conclude safe use. Available hazard data do not support the need for a DNEL to be established for other health effects. Users are advised to consider national Occupational Exposure Limits or other equivalent values.

4. Guidance to check compliance with the exposure scenario (Health 1)

Where other Risk Management Measures/Operational Conditions are adopted, then users should ensure that risks are managed to at least equivalent levels.

Exposure scenario

Use as a Fuel - Professional

Identification

Product name	Kerosines
Version number	2018
Es reference	ES12b

1. Title of exposure scenario

Main title	Use as a Fuel - Professional
Process scope	Covers the use as a fuel (or fuel additive) and includes activities associated with its transfer, use, equipment maintenance and handling of waste.

Environment

Environmental release category	ERC9a Widespread use of functional fluid (indoor) ERC9b Widespread use of functional fluid (outdoor)
--------------------------------	---

SPERC	ESVOC SPERC 9.12b.v1
-------	----------------------

Worker

Process category	PROC1 Chemical production or refinery in closed process without likelihood of exposure or processes with equivalent containment conditions PROC2 Chemical production or refinery in closed continuous process with occasional controlled exposure or processes with equivalent containment conditions PROC3 Manufacture or formulation in the chemical industry in closed batch processes with occasional controlled exposure or processes with equivalent containment condition PROC8a Transfer of substance or mixture (charging and discharging) at non-dedicated facilities PROC8b Transfer of substance or mixture (charging and discharging) at dedicated facilities PROC16 Use of fuels
------------------	---

2. Conditions of use affecting exposure (Industrial - Environment 1)

Product characteristics

Substance is complex UVCB. Predominantly hydrophobic.

Amounts used

Fraction of EU tonnage used in region: 0.1
Regional use tonnage: 4,600,000 tonnes/year
Fraction of Regional tonnage used locally: 1
Annual site tonnage: 2300 tonnes
Maximum daily site tonnage: 6.4 tonnes

Frequency and duration of use

Continuous release.
Emission days: 365 days/year

Other given operational conditions affecting environmental exposure

Emission factor - air	Release fraction to air from wide dispersive use (regional only): 1.0E-03
Emission factor - water	Release fraction to wastewater from wide dispersive use: 1.0E-05
Emission factor - soil	Release fraction to soil from wide dispersive use (regional only): 1.0E-05

Environmental factors not influenced by risk management measures

Use as a Fuel - Professional

Dilution Local freshwater dilution factor: 10
Local marine water dilution factor: 100

Risk management measures

Good practice Common practices vary across sites, thus conservative process release estimates used.
Risk from environmental exposure is driven by fresh water.

STP type Municipal STP.

STP details Estimated substance removal from wastewater via domestic sewage treatment: 95.0%
Removal efficiency (total): 95.0%
Maximum allowable site tonnage (M_{safe}), based on release following total wastewater treatment removal: 2.9E+05 kg/day
Assumed domestic sewage treatment plant flow (m³/day):
2000.

Technical onsite conditions and measures to reduce or limit discharges to air, water and soil

Air Treat air emission to provide a typical removal efficiency of N/A%.

Water Prevent leaks and prevent soil/water pollution caused by leaks. Onsite wastewater treatment required. Treat onsite wastewater (prior to receiving water discharge) to provide the required removal efficiency of (%): 0.0 If discharging to domestic sewage treatment plant, provide the required onsite wastewater removal efficiency of (%): 0.0

Soil Do not apply industrial sludge to natural soils. Sludge should be incinerated, contained or reclaimed.

Conditions and measures related to external treatment of waste for disposal

Waste treatment Combustion emissions limited by required exhaust emission controls. Combustion emissions considered in regional exposure assessment.

Conditions and measures related to external recovery of waste

Recovery method This substance is consumed during use and no waste of the substance is generated.

2. Conditions of use affecting exposure (Workers - Health 1)

Product characteristics

Physical state Liquid

Vapour pressure Vapour pressure 0.5 - 10 kPa at STP.

Concentration details Covers percentage substance in the product up to 100% (unless stated differently).

Frequency and duration of use

Covers daily exposures up to 8 hours (unless stated differently).

Other given operational conditions affecting workers exposure

Setting Assumes a good basic standard of occupational hygiene is implemented.

Temperature Assumes use at not more than 20°C above ambient temperature, unless stated differently.

Organisational measures to prevent/limit releases, dispersion and exposure

Organisational measures General measures (skin irritants) Avoid direct skin contact with product. Identify potential areas for indirect skin contact. Wear gloves (tested to EN374) if hand contact with substance likely. Clean up contamination/spills as soon as they occur. Wash off any skin contamination immediately. Provide basic employee training to prevent/minimise exposures and to report any skin problems that may develop.

Use as a Fuel - Professional

Risk management measures

General exposures (closed systems)
No other specific measures identified.

.
Use as a fuel
(closed systems)
No other specific measures identified.

.
Bulk transfers
No other specific measures identified.

.
Transfer from/pouring from containers
No other specific measures identified.

.
Equipment cleaning and maintenance
No other specific measures identified.

.
Bulk product storage
No other specific measures identified.

3. Exposure estimation (Environment 1)

Assessment method	Used Petrorisk model. (Hydrocarbon Block Method)
	Maximum Risk Characterisation Ratios for air emissions 4.4E-04 Maximum Risk Characterisation Ratios for wastewater emissions 3.4E-03

4. Guidance to check compliance with the exposure scenario (Environment 1)

Guidance is based on assumed operating conditions which may not be applicable to all sites, thus, scaling may be necessary to define appropriate site-specific risk management measures. Required removal efficiency for wastewater can be achieved using onsite/offsite technologies, either alone or in combination. Required removal efficiency for air can be achieved using onsite technologies, either alone or in combination. Further details on scaling and control technologies are provided in SpERC factsheet (<http://cefic.org/en/reach-for-industries-libraries.html>).

3. Exposure estimation (Health 1)

Assessment method	The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise indicated
	Available hazard data do not enable the derivation of a DNEL for dermal irritant effects. Qualitative approach used to conclude safe use. Available hazard data do not support the need for a DNEL to be established for other health effects. Users are advised to consider national Occupational Exposure Limits or other equivalent values.

4. Guidance to check compliance with the exposure scenario (Health 1)

Where other Risk Management Measures/Operational Conditions are adopted, then users should ensure that risks are managed to at least equivalent levels.